

Eric L. Wesenberg, Bar No. 139696
EWesenberg@perkinscoie.com
Christopher L. Kelley, Bar No. 166608
CKelley@perkinscoie.com
Kenneth J. Halpern, Bar No. 187663
KHalpern@perkinscoie.com
Wing H. Liang, Bar No. 285521
WLiang@perkinscoie.com
PERKINS COIE LLP
3150 Porter Drive
Palo Alto, CA 94304-1212
Telephone: 650.838.4300
Facsimile: 650.838.43501

Attorneys for Plaintiff
THX, Ltd.

UNITED STATES DISTRICT COURT
NORTHERN DISTRICT OF CALIFORNIA
SAN JOSE DIVISION

THX, Ltd.,

Plaintiff,

v.

APPLE, INC.,

Defendant.

ORIGINAL FILED

MAR 14 2013

Richard W. Wieking
Clerk, U.S. District Court
Northern District of California
San Jose

Case No. **CV13- 1161** JSW
**COMPLAINT FOR PATENT
INFRINGEMENT**
DEMAND FOR JURY TRIAL

1 Plaintiff THX Ltd. ("THX") by and through its undersigned attorneys, for its complaint
2 against defendant Apple Inc. ("Apple"), hereby alleges as follows:

3 1. This is an action for patent infringement arising under the Patent Laws of
4 the United States, 35 U.S.C. § 1 *et seq.*

5 THE PARTIES

6 2. Plaintiff THX is a corporation duly organized and existing under the laws
7 of the State of Delaware, with its principal place of business at 1600 Los Gatos Drive, San
8 Rafael, California 94903.

9 3. On information and belief, defendant Apple is a corporation organized and
10 existing under the laws of the State of California with its principal place of business at 1 Infinite
11 Loop, Cupertino, California.

12 JURISDICTION AND VENUE

13 4. This Court has jurisdiction over this patent infringement action pursuant to
14 28 U.S.C. §§ 1331 and 1338(a).

15 5. This Court has specific and/or general personal jurisdiction over Apple
16 because Apple is doing business in this District and has committed acts giving rise to this action
17 within this District.

18 6. Venue is proper in this District pursuant to 28 U.S.C. § 1391 and 1400
19 because Apple does business in the State of California and this District, Apple has committed acts
20 giving rise to this action in the State of California and this District, a substantial part of the events
21 or omissions giving rise to THX's claims happened in this District, and Apple is subject to
22 personal jurisdiction in this District.

23 INTRADISTRICT ASSIGNMENT

24 7. Intradistrict assignment is proper in San Jose because a substantial part of
25 the acts giving rise to the claims asserted herein occurred in Santa Clara County and because
26 Apple maintains its principal place of business in Santa Clara County.

FIRST CLAIM FOR RELIEF

(Infringement of United States Patent No. 7,433,483)

8. On October 7, 2008, the United States Patent and Trademark Office duly and lawfully issued United States Patent No. 7,433,483 ("the '483 patent"). The '483 patent is entitled "Narrow Profile Speaker Configurations and Systems." A copy of the '483 patent is attached hereto as Exhibit A.

9. THX is the owner and assignee of all right, title, and interest in and to the '483 patent.

10. Apple has been and now is infringing the '483 patent in the State of California and elsewhere in the United States by, among other things, making, using, importing, offering to sell, and/or selling in the United States products covered by one or more claims of the '483 patent in violation of 35 U.S.C. § 271, including but not limited to Apple's iPhone 4 and later models, as well as its iPad, and iMac products, which incorporate narrow-profile speaker units that output sound through a duct or aperture having a narrow dimension.

11. Apple's infringement of the '483 patent has caused and will continue to cause THX both monetary damage and irreparable harm for which it has no adequate remedy at law.

PRAYER FOR RELIEF

Accordingly, plaintiff THX respectfully requests that this Court enter judgment against defendant Apple as follows:

12. Declaring that Apple has infringed the '483 patent;

13. Permanently enjoining Apple and its respective officers, directors, agents, servants, affiliates, employees, divisions, branches, subsidiaries, parents, and all others acting in active concert therewith from infringement of the '483 patent;

14. Awarding damages in an amount adequate to compensate THX for Apple's infringement, consisting of, inter alia, THX's lost profits, but in any event at least a reasonable royalty; and

Plaintiff respectfully demands a jury trial on all issues so triable.

PERKINS COIE LLP

By: Eric L. Wesenberg *ELW*
Eric L. Wesenberg
EWesenberg@perkinscoie.com

Attorneys for Plaintiff
THX, Ltd.

EXHIBIT A

(12) **United States Patent**
Fincham

(10) **Patent No.:** **US 7,433,483 B2**
(45) **Date of Patent:** **Oct. 7, 2008**

(54) **NARROW PROFILE SPEAKER CONFIGURATIONS AND SYSTEMS**

3,617,654 A 11/1971 Heidrich 381/346

(75) Inventor: **Lawrence R. Fincham**, Santa Rosa, CA (US)

(Continued)

(73) Assignee: **THX Ltd.**, San Rafael, CA (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 140 days.

EP 0404 117 A2 12/1990

(Continued)

(21) Appl. No.: **10/937,796**

OTHER PUBLICATIONS

(22) Filed: **Sep. 8, 2004**

(65) **Prior Publication Data**

US 2005/0129258 A1 Jun. 16, 2005

Lopez, Jose, et al., "3-D Audio With Dynamic Tracking For Multimedia Environments," Universidad Politecnica de Valencia, Departamento de Comunicaciones, Grao de Gandia, Spain, 2nd COST-G6 Workshop on Digital Audio Effects (DAFx99), Dec. 9-11, 1999, Trondheim, Norway.

Related U.S. Application Data

(Continued)

(63) Continuation-in-part of application No. 10/339,357, filed on Jan. 8, 2003, which is a continuation-in-part of application No. 10/074,604, filed on Feb. 11, 2002, now Pat. No. 7,254,239.

Primary Examiner—Brian Ensey
(74) *Attorney, Agent, or Firm*—Irell & Manella LLP

(60) Provisional application No. 60/267,952, filed on Feb. 9, 2001, provisional application No. 60/331,365, filed on Jan. 8, 2002.

(57) **ABSTRACT**

(51) **Int. Cl.**
H04R 1/02 (2006.01)

(52) **U.S. Cl.** 381/337; 381/345; 381/347

(58) **Field of Classification Search** 381/337, 381/345, 347, 349, 350, 352, 386, 87, 89, 381/304, 308, 332, 336, 338, 339, 341; 181/179, 181/184, 185, 186, 199

See application file for complete search history.


A narrow profile speaker unit comprises at least one speaker outputting sound towards an internal surface and through a duct with an output terminus, such as a slot, having a narrow dimension, effectively changing the cross-section of the speaker's audio output wave. A pair of speakers may face one another, outputting sound towards a common output slot. Multiple pairs of speakers may be used to form an inline speaker unit for increased sound output. A slotted speaker unit may include multiple speakers facing the same direction, towards a groundplane or reflecting surface, and having parallel apertures for allowing sound radiation. The speaker units may be integral with or attached to electronic appliances such as desktop computers or flatscreen devices, or may be used in automobiles or other contexts.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,440,078 A 4/1948 Devine 181/31
3,371,742 A * 3/1968 Norton et al. 181/153

33 Claims, 20 Drawing Sheets



US 7,433,483 B2

Page 2

U.S. PATENT DOCUMENTS

4,016,953	A	4/1977	Butler	381/89
4,029,170	A *	6/1977	Phillips	181/155
4,131,179	A	12/1978	Pope	181/156
4,308,423	A	12/1981	Cohen	381/1
4,334,593	A	6/1982	Sechrist	181/144
4,398,619	A	8/1983	Daniel	181/156
4,509,184	A	4/1985	Yanagawa	381/308
4,574,906	A *	3/1986	White et al.	381/348
4,620,317	A	10/1986	Anderson	381/90
4,628,528	A	12/1986	Bose et al.	381/90
4,837,839	A	6/1989	Andrews	381/199
4,846,382	A	7/1989	Foultnier et al.	224/42.42
5,036,946	A	8/1991	Yoshino	181/156
5,067,159	A	11/1991	Kasai et al.	381/90
5,115,470	A	5/1992	Sutheim	381/76
5,138,526	A	8/1992	Chung Hsiang	361/392
5,199,075	A	3/1993	Fosgate	381/24
5,225,639	A	7/1993	Kobayashi et al.	181/151
5,253,301	A	10/1993	Sakamoto et al.	381/89
5,306,880	A	4/1994	Coziar et al.	181/149
5,400,408	A	3/1995	Lundgren et al.	381/88
5,432,860	A	7/1995	Kasajima et al.	381/156
5,451,726	A	9/1995	Haugum	181/150
5,471,018	A	11/1995	Nieuwendijk et al.	181/152
5,561,717	A	10/1996	Lamm	381/89
5,590,208	A	12/1996	Koyano et al.	381/338
5,610,992	A	3/1997	Hickman	381/188
5,657,391	A	8/1997	Jyosako	381/1
5,661,808	A	8/1997	Klayman	381/1
5,677,957	A	10/1997	Hulsebus	381/1
5,727,066	A	3/1998	Elliott et al.	381/1
5,749,433	A	5/1998	Jackson	181/156
5,862,227	A	1/1999	Orduna-Bustamante et al.	381/17
5,870,484	A	2/1999	Greenberger	381/300
5,870,485	A	2/1999	Lundgren et al.	381/306
5,902,023	A	5/1999	Yu et al.	312/7.2
5,929,393	A	7/1999	Jeter, Jr.	181/199
5,930,376	A	7/1999	Markow et al.	381/333
5,943,431	A	8/1999	Weiss et al.	381/305
5,949,894	A	9/1999	Nelson et al.	381/300
6,198,826	B1	3/2001	Cowieson et al.	381/18
6,307,947	B1	10/2001	Wiener	381/386
6,363,157	B1 *	3/2002	Chick	381/89
6,771,787	B1	8/2004	Hoefler et al.	381/338
2002/0085731	A1	7/2002	Aylward	381/349
2002/0153193	A1	10/2002	Toki	181/148
2002/0154783	A1	10/2002	Fincham	381/17
2003/0219137	A1	11/2003	Fincham	381/302

FOREIGN PATENT DOCUMENTS

GB	2 074 823	A	11/1981
JP	52-004202		1/1977
JP	56-016400		2/1981
JP	56-162600		12/1981
JP	63-502945		10/1988
JP	64-018396		1/1989
JP	04-137994		5/1992
JP	05-014993		1/1993
JP	08-154300		6/1996
JP	11-252698		9/1999
JP	11-318000		11/1999
JP	2000-078700		3/2000
WO	WO 87/06090		10/1987
WO	WO 94/01981		1/1994
WO	WO 00/25618		5/2000

WO

WO 00/67522

11/2000

OTHER PUBLICATIONS

Brown, C. Phillip, et al., "A Structural Model for Binaural Sound Synthesis," IEEE Transactions on Speech and Audio Processing, vol. 6, No. 5, Sep. 1998.

Jost, Adrian, et al., "Transaural 3-D With User-Controlled Calibration," Proceedings of the COST G-6 Conference on Digital Audio Effects (DAFX-00), Verona, Italy, Dec. 7-9, 2000.

Jot, Jean-Marc, "Synthesizing Three-Dimensional Sound Scenes in Audio or Multimedia Production and Interactive Human-Computer Interfaces," 5th International Conference: Interface to Real & Virtual Worlds, Montpellier, France, May 1996.

Kyriakakis, Chris, "Fundamental and Technological Limitations of Immersive Audio Systems," Proceedings of the IEEE, vol. 86, No. 5, May 1998.

Kendall, Gary S., "A 3D Sound Primer," Center for Music Technology, School of Music, Northwestern University, printout from website (www.northwestern.edu/musicschool/classes/3D/pages/sndPrmGK.html), printed Jan. 4, 2002.

Soebo, Asbjorn, "Effect of Early Reflections in Binaural Systems With Loudspeaker Reproduction," Acoustics Group, Department of Telecommunications, Norwegian University of Science and Technology (NTNU), Proc. 1999 IEEE Workshop on Applications of Signal Processing to Audio and Acoustics, New Paltz, New York, Oct. 17-20, 1999.

Zurek, P.M., "The Precedence Effect," *Directional Hearing*, Springer-Verlag, New York, 1987, pp. 85-105.

Trahiotis, Bernstein, "Some Modern Techniques and Devices Used to Preserve and Enhance the Spatial Qualities of Sound," *Directional Hearing*, Springer-Verlag, New York, 1987, pp. 279-290.

"Virtual Acoustics Project," Institute of Sound and Vibration Research, University of Southampton, printout from website (www.isvr.soton.ac.uk/FDAG/vap/), Feb. 4, 1998.

Kahana, et al., "Multi-Channel Sound Reproduction using a Four-Ear Dummy-Head," presented at the 102nd Audio Engineering Society Convention, Mar. 22-25, 1997, Munich, Germany.

Kahana, et al., "Objective and Subjective Assessment of Systems for the Production of Virtual Acoustic Images for Multiple Listeners," presented at the 102nd Audio Engineering Society Convention, Mar. 22-25, 1997, Munich, Germany.

Kahana, et al., "A Multiple Microphone Recording Technique for the Generation of Virtual Acoustic Images," *Journal of the Acoustic Society of America*, vol. 105, No. 3, Mar. 1999, pp. 1503-1516.

Kirkeby, et al., "Local Sound Field Reproduction using Digital Signal Processing," *Journal of the Acoustical Society of America*, vol. 100, No. 3, Sep. 1996, pp. 1584-1593.

Kirkeby, et al., "Virtual Source Imaging Over Loudspeakers," Proceedings of the Institute of Acoustics, vol. 19: Part 6, 1997.

Kirkeby, et al., "The 'Stereo Dipole': Binaural Sound Reproduction using Two Closely Spaced Loudspeakers," presented at the 102nd Audio Engineering Society Convention, Mar. 22-25, 1997, Munich, Germany.

Kirkeby, et al., "Acoustic Fields Generated by Virtual Source Imaging Systems," Proceedings of Active 97, The 1997 International Symposium on Active Control of Sound and Vibration, Aug. 21-23, 1997, Budapest, Hungary, pp. 941-954.

Nelson, et al., "Adaptive Inverse Filters for Stereophonic Sound Reproduction," IEEE Transactions on Signal Processing, vol. 40, No. 7, Jul. 1992, pp. 1621-1632.

Nelson, P. A., "Active Control of Acoustic Fields and the Reproduction of Sound," *Journal of Sound and Vibration*, vol. 177, No. 4, Nov. 3, 1994, pp. 447-477.

Nelson, et al., "Inverse Filter Design and Equalization Zones in Multichannel Sound Reproduction," IEEE Transactions on Speech and Audio Processing, vol. 3, No. 3, May 1995, pp. 185-192.

Nelson, et al., "Multichannel Signal Processing Techniques in the Reproduction of Sound," *Journal of the Audio Engineering Society*, vol. 44, No. 11, Nov. 1996, pp. 973-989.

Nelson, et al., "Experiments on a System for the Synthesis of Virtual Acoustic Sources," *Journal of the Audio Engineering Society*, vol. 44, No. 11, Nov. 1996, pp. 990-1007.

US 7,433,483 B2

Page 3

Nelson, et al, "Sound Fields for the Production of Virtual Acoustic Images," *Journal of Sound and Vibration*, vol. 204, No. 2, 1997, pp. 386-396.

Takeuchi, et al, "The Effects of Reflections on the Performance of Virtual Acoustic Imaging Systems," *Proceedings of Active 97, The 1997 International Symposium on Active Control of Sound and Vibration*, Aug. 21-23, 1997, Budapest, Hungary, pp. 927-940.

"LDSG Introduction—Enclosure designs," sponsored by Sonic Craft, Jul. 17, 2002.

P. Messenger, "KEF's Kameleon," *Hi-Fi News & Record Review*, Sep. 1984, pp. 29, and last page.

U.S. Appl. No. 11/416,626, filed May 2006, Fincham.

P. Messenger, "KEF's Kameleon," *Hi-Fi News & Record Review*, Sep. 1984, pp. 29.

M. Colloms, "An Exercise in Conjugation," *Hi-Fi News & Record Review*, Sep. 1984, pp. 53-57.

* cited by examiner

U.S. Patent

Oct. 7, 2008

Sheet 1 of 20

US 7,433,483 B2




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3A

U.S. Patent

Oct. 7, 2008

Sheet 2 of 20

US 7,433,483 B2




FIG. 3B




FIG. 3C




FIG. 4A







FIG. 4B

U.S. Patent

Oct. 7, 2008

Sheet 3 of 20

US 7,433,483 B2







**FIG. 5****FIG. 6****FIG. 7**



U.S. Patent

Oct. 7, 2008

Sheet 4 of 20

US 7,433,483 B2

**FIG. 9A****FIG. 9B****FIG. 9C****FIG. 9D****FIG. 9E**




*FIG. 10A**FIG. 10B*

U.S. Patent

Oct. 7, 2008

Sheet 6 of 20

US 7,433,483 B2





**FIG. 11****FIG. 13A****FIG. 13B**




U.S. Patent

Oct. 7, 2008

Sheet 7 of 20

US 7,433,483 B2

**FIG. 12A****FIG. 12B****FIG. 12C****FIG. 12D**

**FIG. 14****FIG. 15****FIG. 16**

U.S. Patent

Oct. 7, 2008

Sheet 9 of 20

US 7,433,483 B2




FIG. 17A




FIG. 17B




FIG. 17C





FIG. 18

U.S. Patent


Oct. 7, 2008

Sheet 11 of 20

US 7,433,483 B2



Direction Of Sound



FIG. 19A**FIG. 19B**

U.S. Patent

Oct. 7, 2008

Sheet 12 of 20

US 7,433,483 B2

**FIG. 20****FIG. 21**

U.S. Patent

Oct. 7, 2008

Sheet 13 of 20

US 7,433,483 B2




FIG. 22

U.S. Patent

Oct. 7, 2008

Sheet 14 of 20

US 7,433,483 B2




FIG. 23A




FIG. 23B




FIG. 24

U.S. Patent

Oct. 7, 2008

Sheet 16 of 20

US 7,433,483 B2




FIG. 25




FIG. 26A




FIG. 26B

U.S. Patent

Oct. 7, 2008

Sheet 17 of 20

US 7,433,483 B2

FIG. 27





FIG. 28A




FIG. 28B




FIG. 29

U.S. Patent

Oct. 7, 2008

Sheet 19 of 20

US 7,433,483 B2




FIG. 30B




FIG. 30A

U.S. Patent

Oct. 7, 2008

Sheet 20 of 20

US 7,433,483 B2




FIG. 30C

US 7,433,483 B2

1

NARROW PROFILE SPEAKER CONFIGURATIONS AND SYSTEMS

RELATED APPLICATION INFORMATION

This application is a continuation-in-part application of U.S. application Ser. No. 10/339,357 filed Jan. 8, 2003, which is a continuation-in-part application of utility application U.S. application Ser. No. 10/074,604 filed on Feb. 11, 2002 now U.S. Pat. No. 7,254,239, (which claims the benefit of U.S. Provisional Application Ser. No. 60/267,952, filed on Feb. 9, 2001), and which further claims the benefit of U.S. Provisional Application Ser. No. 60/331,365, filed Jan. 8, 2002, and of PCT Application Ser. No. PCT/US02/03880, filed on Feb. 8, 2002, all of which are hereby incorporated by reference as if set forth fully herein.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The field of the present invention relates to sound reproduction and, more specifically, to speaker configurations and enclosures, and related sound processing.

2. Background

Sound reproduction systems incorporating speakers are commonplace in homes, theaters, automobiles, places of entertainment, and elsewhere. The number, size, quality, characteristics, and arrangement of speakers affect sound quality in virtually any listening environment. However, many environments have constraints which limit the number, size, or type of speakers which can be used, and their arrangement. These constraints may be technical, mechanical, or aesthetic in nature.

For example, with respect to consumer products such as computers and televisions, there may be limited space to physically attach or integrate speakers. A common practice is to provide a set of external speakers separate from the enclosure of the computer, television, or other product, allowing the user the ability to place the speakers widely apart and thus achieve a true stereo effect. However, loose speakers take up space on a desk or table, and require unsightly or inconvenient electrical connections to the computer, television, or other product. Moreover, use of such additional external speakers generally requires the consumer to purchase them separately from the main product itself, thus increasing cost. In addition, space restrictions on a desk or table may limit the possible locations of speakers, and/or their number, size and orientation, and thus adversely affect sound quality including the desired stereo effect.

For consumer items such as laptop computers, the option of utilizing external speakers to improve sound quality may not be possible.

Confined listening areas also create constraints which can impact sound quality, and can often be unsuitable for optimal sound reproduction. For example, the listening space of an automobile creates particular challenges and problems for quality sound reproduction. These problems partially result from the unique sound environment of the automobile when compared with a good listening room. Among the disadvantages are:

Much smaller internal volume resulting in a reduced reverberation time and lower modal density at low frequencies resulting in a lack of ambience and an uneven bass response.

The proximity of highly reflective surfaces (such as the windows) to highly absorptive areas such as the upholstery or the occupants' clothing leads to a great variability

2

with frequency and head position of the direct to indirect sound arriving at the listener. Consequently even small changes in head or seating position can cause significant and undesirable changes in the timbral quality of the music.

The listening positions are necessarily restricted to the seating positions provided (usually 4 or 5) and all of these are very asymmetrically placed with respect to the speaker positions. Space is always at a premium within a car interior and as a result the speakers are often placed in physically convenient positions, that are nevertheless very poor from an acoustic point of view, such as the foot wells and the bottom of the front and rear side doors. As a result the listener's head is always much closer to either the left or right speaker leading directly large inter-channel time differences and different sound levels due to the 1/r law.

Additionally, the angles between the axes from the listener's ears to the axes of symmetry of the left and right speakers is quite different for each occupant. The perceived spectral balance is different for each channel due to the directional characteristics of the drive units. Masking of one or more speakers by the occupants' clothes or legs can often result in the attenuation of the mid- and high-frequencies by as much as 10 dB.

The conditions noted above tend to adversely impact the ability to produce high quality stereo reproduction, which ideally has the following attributes:

A believable and stable image or soundstage resulting from the listener being nearly equidistant from the speakers reproducing the left and right channels and a sufficiently high ratio of direct-to-indirect sound at the listener's ears.

A smooth timbral balance at all the listening positions.

A sense of ambience resulting from a uniform soundfield.

Some features are provided in automobile audio systems which can partially mitigate the aforementioned problems. For example, an occupant can manually adjust the sound balance to increase the proportional volume to the left or right speakers. Some automobile audio systems have a "driver mode" button which makes the sound optimal for the driver. However, because different listening axes exist for left and right occupants, an adjustment to the balance that satisfies the occupant (e.g., driver) on one side of the automobile will usually make the sound worse for the occupant seated on the other side of the automobile. Moreover, balance adjustment requires manual adjustment by one of the occupants, and it is generally desirable in an automobile to minimize user intervention.

Another modification made to some automobile audio systems is to provide a center speaker, which reduces the image instability that occurs when the listener is closer to either the left or right speaker when both are reproducing the same mono signal, with the intention of producing a central sound image. Yet another possible approach is adding more speakers in a greater variety of positions (e.g., at the seat tops). While such techniques can sometimes provide a more pleasing effect, they cannot provide stable imaging as the problems associated with asymmetry described above still remain. The considerable additional cost of such design approaches is usually undesirable in markets such as the highly cost sensitive and competitive automotive industry. Moreover, as previously noted, space is usually at a premium in the automobile interior, and optimal speaker positions are limited.

The aforementioned problems are not limited to sound systems designed for automobiles, but may exist in other confined spaces as well. Even in larger spaces, it may be

US 7,433,483 B2

3

difficult to achieve ideal sound reproduction due to constraints on where speakers may be located, or other considerations. Freestanding speakers can take up valuable room space, while speakers embedded in walls and ceilings require a large cross-sectional areas and may be aesthetically displeasing. More generally, in many environments it is desirable to minimize the visual impact of speakers in a sound reproduction system. One technique, for example, is to color or otherwise decorate the protective speaker faceplate to match the surrounding wall or object in which the speaker is placed, or to hide speakers behind an artificial painting. These types of solutions may not be satisfactory for all consumers, and may limit the possibilities for optimal speaker placement as well.

It would therefore be advantageous to provide an improved sound reproduction and/or speaker system which overcomes the foregoing problems, and/or provides other benefits and advantages.

SUMMARY OF THE INVENTION

Certain embodiments disclosed herein are generally directed, in one aspect, to a sound reproduction system having a speaker configuration and/or enclosure which provides a relatively narrow sound output region in relation to the size of the speaker face(s) utilized in the sound reproduction system. In some embodiments, a reflecting surface disposed immediately in front of the face of the speaker cone redirects the sound output, through a sound duct or otherwise, and causes the sound to emanate from a slot or other aperture. Single or multiple speaker embodiments are possible, with a single or multiple slots or other apertures. Sound-damping material may be added to define a sound duct, preferably around the periphery of the speaker cone(s), so as to influence the directivity of the sound waves towards the output slot or aperture, and/or to reduce potentially interference.

Further embodiments, variations and enhancements are also disclosed herein.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an oblique frontal view diagram of a narrow profile speaker unit having a slot for sound output, in accordance with one embodiment as disclosed herein.

FIGS. 2A and 2B are front and side view diagrams, respectively, of the narrow profile speaker unit of FIG. 1.

FIGS. 3A, 3B, and 3C are diagrams of cross-sectional top views of alternative embodiments of the enclosure of the speaker unit of FIG. 1 with different arrangements of sound damping material in the enclosure.

FIGS. 4A and 4B are diagrams of oblique and side views, respectively, of a cylindrical speaker unit having a sound output slot, in accordance with one embodiment as disclosed herein.

FIG. 5 is a diagram of an example of a speaker system utilizing cylindrical speaker units illustrated in FIG. 4.

FIG. 6 is a side view of another embodiment of a narrow profile speaker unit in accordance with one embodiment as disclosed herein.

FIG. 7 is a diagram illustrating sound radiating from a slotted speaker unit into a room of listeners, according to a particular example.

FIG. 8 is a cross-sectional side view diagram of a speaker unit having a sound output slot, according to another embodiment as disclosed herein.

FIGS. 9A through 9E are top view cross-sectional diagrams illustrating various arrangements of relative speaker

4

locations and sound damping material, as may be used in connection with the speaker unit illustrated in FIG. 8.

FIGS. 10A and 10B are diagrams comparing the radiance of sound from a ground plane speaker unit constructed in accordance with the principles illustrated in FIG. 8, with a conventional speaker unit.

FIG. 11 is a diagram of a speaker unit having multiple speakers, with sound output slot(s).

FIG. 12A is a front cut-away view of an embodiment of a speaker enclosure for a pair of stereo speakers.

FIG. 12B is a top cross-sectional view diagram of the speaker enclosure shown in FIG. 12A.

FIG. 12C is an oblique front view diagram of the speaker enclosure shown in FIGS. 12A and 12B.

FIG. 12D is a diagram illustrating sound reflection from a downward oriented speaker, such as a speaker in the speaker enclosure of FIGS. 12A-12C.

FIG. 13A is a diagram of a speaker unit having multiple speakers and a sound output slot in accordance with another embodiment, and FIG. 13B is a diagram of a sound processing system that may be used in connection with the speaker unit of FIG. 13A.

FIG. 14 is a simplified block diagram of a sound processing system in accordance with one or more embodiments as disclosed herein.

FIG. 15 is a diagram of a speaker arrangement including pairs of speakers facing one another, with sound output slot(s), in accordance with one embodiment as disclosed herein.

FIG. 16 is a diagram illustrating an example of a speaker enclosure which may incorporate a speaker arrangement such as illustrated, for example, in FIG. 15.

FIGS. 17A and 17B are diagrams of a speaker arrangement as may be used, for example, in connection with a speaker mounting structure or enclosure for providing sound output through an orifice, and FIG. 17C is a particular variation thereof illustrating preferred dimensions of sound-damping material according to one example.

FIG. 18 is a simplified circuit diagram for the speaker arrangement of FIGS. 17A and 17B, wherein delays are used to synchronize sound output through the orifice.

FIG. 19A is a diagram of a speaker mounting structure or enclosure illustrating a particular arrangement of sound-damping material around the speakers, while FIG. 19B is a detail diagram of a portion of FIG. 19A.

FIG. 20 is a cutaway top-view diagram of another speaker arrangement similar to FIG. 17A but adding an additional speaker.

FIG. 21 is an oblique view diagram of the speaker arrangement of FIG. 20, illustrating one possible embodiment of a speaker mounting structure associated therewith.

FIG. 22 is an assembly diagram of a speaker mounting structure utilizing a general speaker arrangement such as shown in FIG. 20.

FIGS. 23A and 23B are oblique view diagrams comparing speaker mounting structures utilizing the general speaker arrangements of FIGS. 12A-12B and 19A-19B, respectively.

FIG. 24 is a diagram showing an example of a stereo unit 2400 adapted for convenient installation in a vehicle.

FIG. 25 is a top-view cross-sectional diagram of a speaker arrangement including an array of speakers with sound output slot(s), in accordance with one embodiment as disclosed herein.

FIGS. 26A and 26B are cross-sectional diagrams of a side view and a front view, respectively, of a flatscreen display device having speaker arrays with sound output slot(s).

FIG. 27 is an oblique view diagram of a speaker unit having an array of speakers and sound output slot(s).

US 7,433,483 B2

5

FIGS. 28A and 28B are a side view cross-sectional diagram and an oblique view diagram, respectively, of a speaker unit having a slot for sound output, in accordance with another embodiment as disclosed herein.

FIG. 29 is a diagram of a sound processing system generally in accordance with various principles described with respect to FIG. 14, and showing examples of possible transfer function characteristics for certain processing blocks.

FIGS. 30A-30C are graphs illustrating examples of gain and/or phase transfer functions for a sound processing system in accordance with FIG. 29.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Certain embodiments disclosed herein are generally directed, in one or more aspects, to a speaker configuration or enclosure for a sound reproduction system which provides a relatively narrow sound output region in relation to the size of the speaker face(s) utilized in the sound reproduction system. In some embodiments, a reflecting surface disposed immediately in front of the face of the speaker cone redirects the sound output, through a sound duct or otherwise, and causes the sound to emanate from a slot or other aperture. In some instances, such a configuration allows the speaker(s) to be hidden from view, provides a relatively broad directional characteristic, allows a larger speaker to be used in a confined installation space than would otherwise be convenient or possible, and/or provides other benefits or advantages. Single or multiple speaker embodiments are possible, allowing a wide variety of potential speaker arrangements.

Embodiments as disclosed herein may be employed in a variety of applications, and may be particularly well suited for situations in which it is desired to conceal speakers from view, or in which audio systems face restrictions with respect to, for example, speaker locations or installation area. In certain multiple speaker embodiments, a plurality of speakers may be mounted along a sound duct, at either the same or variable distances from an output slot or aperture, such that the output from the speakers exits a common output slot or aperture. In some embodiments, as further described herein, the audio signal(s) to the speakers may be processed and/or delayed to ensure that the sound waves generated by each speaker's audio output reinforce rather than interfere with one another. Speakers receiving similar audio signals may be mounted to face each other across a duct, either directly or separated by, for example, a frammel (such as a sound-blocking baffle between two proximal speakers). Arrays of opposing speakers may be configured using the same principles. The use of a narrow profile speaker enclosure may be in connection with other speakers, such as tweeters, to further enhance the sound quality experienced by the listener. The speaker configuration may be advantageously employed in applications such as electronic devices, desktop computer monitors, and so on, or any application in which a low speaker profile may be advantageous or desirable.

FIG. 1 is a diagram of a narrow profile speaker unit 100 having a slot for sound output, and illustrated from an oblique frontal view, in accordance with one or more embodiments as disclosed herein. In FIG. 1, a speaker 107 is supported by a baffle 101 comprising a mounting surface (or other barrier) 102, a sound reflecting surface 103 disposed preferably in parallel orientation to the mounting surface 102, and side walls 104 and 105, which collectively define a sound duct 115 having an output slot (or other orifice) 106 for radiating sound produced by the speaker 107. The baffle 101 in FIG. 1 is adapted to receive the cone of the speaker 107 such that the

6

primary acoustic output of the speaker 107 is directed towards the sound reflecting surface 103, and ultimately emanated from the output slot 106. The presence of mounting surface (or other barrier) 102 may provide the desirable effect of, among other things, acoustically isolating the speaker's rear radiation from its front radiation.

The speaker 107 may receive an audio input signal from any audio signal source such as, for example, a CD player, cassette player, radio, etc., with or without intervening sound processing. The audio input signal may also optionally be applied, either directly or via a sound processor, to additional drivers or other speakers (not shown).

FIGS. 2A and 2B are front and side view diagrams, respectively, of the speaker unit 100 of FIG. 1. FIG. 2B, in particular, illustrates the direction of sound output (shown as an arrow) from the output slot 106, generally perpendicular to the sound reflecting surface 103 and the front face of the speaker 107. Preferably, the sound reflecting surface 103 is spaced at a distance from the front face of the speaker 107 such that the duct or chamber 115 defined by the surrounding sidewalls 104, 105 and backwall 112 does not permit soundwaves of the primary acoustic output from the speaker 107 to unfold significantly within the confines of the duct 115, as pressure effects will tend to cause the lateral soundwaves that emanate from the output slot 106 to have sound quality and dynamic range comparable to the soundwaves initially emitted from the speaker 107 itself.

The output slot (or other orifice) 106 may be of any suitable shape, but is preferably configured so as to provide a relatively narrow profile from which sound of the speaker unit 100 radiates. The output slot 106 may, for example, be generally rectangular in shape (as illustrated in the front view of FIG. 2A), or may be generally oval or elliptical, or may have slightly curved top and/or bottom edges (i.e., the edges of mounting surface 102 and/or sound reflecting surface 103). The output slot 106 is preferably symmetrical and shaped so as to minimize any interference with the desired sound reproduction.

With the speaker unit 100 of FIG. 1, the output slot 106 may be generally configured so as to provide a narrower profile of the effective area from which the soundwaves emanate, as compared to the front face of the speaker 107. As a result, the speaker unit 100 may, for example, utilize a smaller surface area for sound projection, as compared to a conventional forward-oriented speaker. Such a narrower forward profile can provide a number of advantages. From the perspective of speaker arrangement and installation, for example, the speaker unit 100 in various embodiments may find advantageous use in applications having limited space, or where there is a desire to conceal the presence of the speaker(s) from view. For example, a speaker unit with narrow profile sound output slot may find practical use in, e.g. an automobile sound system, and could be placed in a vehicle dashboard or other suitable location. Other advantageous uses are described herein, or would become apparent to those skilled in the art after reviewing the instant specification and drawings.

Besides flexible placement options, another potential benefit of a speaker unit arrangement in accordance with FIG. 1 is that sound emanating from the output slot 106 may generally tend to have a wide dispersion angle along the slot's long axis, as compared to the dispersion angle of a conventional speaker (e.g., a round, forward-oriented speaker face). Thus, the slotted speaker unit 100 may possess an extremely broad directional characteristic over the frequency range for which the wavelength of sound in air is large compared with the slot dimensions. For example, a slot having a dimension of 10×60

7

millimeters may provide a substantially omnidirectional radiation pattern up to 2 to 3 kHz.

Because of the wide dispersion angle along the long axis, a speaker unit **100** in accordance with FIG. **1** may provide a similar listening experience with respect to off-axis listeners at a variety of locations away from the center axis of the output slot **106**. The advantageous dispersion characteristics may permit design choices that, for example, account for the relative likelihood that listeners will be positioned along one or the other axis of the soundwaves emanating from the output slot **106**. These design choices, generally not available for equiaxed drivers, are particularly advantageous in confined listening spaces. In an automobile, for example, wherein listeners are generally confined to their seats, an embodiment of the speaker unit **100** having a horizontally oriented output slot **106** at approximately dashboard level could be installed such that the sound emanating from the slot **106** is characterized by a wide horizontal (left to right) dispersion angle across both the driver and passenger seats, and a narrow vertical dispersion angle that is sufficient to include the upper regions of the driver and passenger seats at a height which the heads of the seated driver and passenger are typically located.

The speaker unit **100** illustrated in FIG. **1** may also be well suited for use in other types of confined areas, particularly where the location of the listeners is predictable in advance. One example of is illustrated in FIG. **7**, which illustrates sound radiating from a slotted speaker unit (such as shown in FIGS. **1** and **2A-2B**) into a room **700** of listeners **721**, **722**. In this example, the speaker unit **704**, shown in side view, is positioned within the ceiling **730** of the room **700**, with the speaker **707** oriented generally perpendicular to the direction of sound radiation. A sound reflecting surface **708** (analogous to **103** in FIGS. **1** and **2A-2B**) defines, along with the face of speaker **707** and various sidewalls and backwall, a relatively narrow duct **713**, and directs the soundwaves towards an output slot in the ceiling **730**. The sound volume quality remains relatively constant regardless of whether listeners are on or off-axis. Moreover, because the sound is radiated from a relatively narrow slot, the presence of the speaker **707** can be substantially concealed. A similar configuration may be used with other speaker units disclosed herein, such as, for example, speaker units illustrated in or described with respect to FIGS. **3A**, **3B**, **3C**, **6**, or others.

In one aspect, the sound duct **115** of speaker unit **100** effectively "turns" the soundwaves output from the speaker **107** by 90° (in this example), so that the sound is carried to the output slot **106** and released while retaining a sufficient degree of sound quality, and modifying the effective shape of the speaker output from an elliptical or circular radiator (as the case may be for speaker **107**) to a rectangular radiator. In addition, the total radiating surface area can be advantageously reduced, as compared to the radiating surface area of the speakers themselves, minimizing the space needed in, e.g., a vehicle dash or other environments. The aspect ratio of the output slot **106** can be adjusted or tailored to modify the directional characteristic of the acoustic output in order to, for example, improve sound quality at off-axis listening positions. While the size and shape of the sound duct **115** and output slot **106** may vary depending upon the particular design goals, there may be physical or practical limitations to how narrow the sound duct **115** and/or output slot **106** may be made. Narrowing of the sound duct **115** and/or output slot **106** may, for example, potentially decrease the efficiency of the speakers (which may be compensated by larger speakers and/or increased drive power), or may cause audible noise from turbulence. Therefore, the narrowness of the sound duct **115** and/or output slot **106** may be limited by, among other things,

8

impedance losses that cannot be made up by increased drive power and the onset of sound artifacts or noise caused by turbulence or nonlinear airflow.

Variations of the speaker unit embodiment illustrated in FIG. **1** are shown in FIGS. **3A**, **3B**, and **3C**, which show cross-sectional top views of a speaker unit with different arrangements of sound damping material in the enclosed chamber or duct **115**. In FIG. **3A**, sidewalls **304**, **305** and backwall **312** of speaker unit **300** are analogous to sidewalls **104**, **105** and backwall **112**, respectively, shown in FIG. **1**. FIG. **3A** illustrates the placement of sound damping material **319** within the duct or chamber (shown as **115** in FIG. **2B**), such that the sound damping material **319** reaches approximately the half-way point along sidewalls **304**, **305**, but is contoured in the middle to circumscribe the periphery of half of the cone of speaker **307**. Sound output from speaker **307** emanates from output slot **306**, as with FIG. **1**. The sound damping material **319** may help prevent, e.g., undesirable interference or reflections within the duct or chamber, that may otherwise be caused by soundwaves reflecting from the backwall **312** or back corners of the chamber, since the soundwaves have no means of egress except the slot **306**. The sound damping material **319** may in certain embodiments also help to prevent the creation of standing waves, and/or minimize the variation of sound output response with respect to frequency so that the speaker output can be readily equalized by, e.g., any standard techniques, including analog or digital equalization. For example, cascaded filter sections may be employed to tailor the frequency response of the speakers **307** in discrete frequency bands so as to provide a relatively uniform overall frequency response.

The sound damping material **319**, in FIG. **3A** and other embodiments as will hereinafter be described, may comprise any suitable material, and is preferably non-resonant in nature, with sound absorbing qualities. The sound damping material **319** may, for example, comprise expanded or compressed foam, or else may comprise rubber, reinforced paper, fabric or fiber, damped polymer composites, or other materials or composites, including combinations of the foregoing materials.

FIG. **3B** illustrates a variation of the speaker unit **300** of FIG. **3A**, but with a different shape of sound damping material **339**. In FIG. **3B**, sidewalls **324**, **325** and backwall **332** of speaker unit **320** are analogous to sidewalls **104**, **105** and backwall **112**, respectively, shown in FIG. **1**. FIG. **3B** illustrates the placement of sound damping material **339** within the duct or chamber (shown as **115** in FIG. **2B**), such that the sound damping material **339** tapers to the approximate end of sidewalls **324**, **325**, and, similar to FIG. **3A**, is contoured to circumscribe the periphery of the cone of speaker **327**. Sound output from speaker **327** emanates from output slot **326**, as with FIG. **1**. The sound damping material **339** serves a similar purpose to sound damping material **319** illustrated in FIG. **3A**, and may further reduce the possibility of reflections from sidewalls **324**, **325** and/or standing (lateral) waves.

FIG. **3C** illustrates another variation of the speaker units **300** and **320** of FIGS. **3A** and **3B**, with yet a different shape of sound damping material **359**. In FIG. **3C**, sidewalls **344**, **345** and backwall **352** of speaker unit **340** are analogous to sidewalls **104**, **105** and backwall **112**, respectively, shown in FIG. **1**. FIG. **3C** illustrates the placement of sound damping material **359** within the duct or chamber (shown as **115** in FIG. **2B**), such that the sound damping material **359** follows along sidewalls **324**, **325** to the edge of the output slot **346** and, similar to FIGS. **3A** and **3B**, is contoured to circumscribe the periphery of the cone of speaker **327**. Sound output from speaker **347** emanates from output slot **346**, as with FIG. **1**.

The sound damping material **359** serves a similar purpose to sound damping material **319** and/or **339** described earlier, but may provide somewhat different sound dispersion characteristics.

Various embodiments of slotted speaker units as described herein may provide a number of advantages, depending potentially upon the specific configuration, environment, and other factors. For example, a slotted speaker unit may have the effect of transforming an elliptical sound radiator (i.e., conventional conical speaker) and effectively transform it into, e.g., a rectangular or almost linear sound radiator, with excellent coverage at the radiated angles. In addition to sound quality, a slotted speaker unit may provide opportunity to improve the packaging and appearance of the speaker unit. As will be described in more detail hereinafter, use of an output slot to radiate sound provides the opportunity for placing speaker outputs very near each other, reducing out-of-phase, cross-cancellation, and lobing effects that may otherwise occur from the use of multiple speakers.

An example another embodiment of a speaker unit in accordance with certain principles of FIG. 1 is illustrated in FIGS. 4A and 4B, which depict oblique and side views, respectively, of a cylindrical speaker unit **400**. The speaker unit **400** comprises a cylindrical housing **405**, roughly can-shaped, in which is placed a speaker **407** positioned such that its cone faces outward from one end of the cylindrical housing **405**. In the example shown, the edge of the cone of the speaker **407** matches the contours of the edge of the cylindrical housing **405**, but in other variations the diameter of the cone may be smaller than the diameter of the cylindrical housing **405**, or else the speaker **407** may be positioned with an offset from (above or below) the top edge of the cylindrical housing **405**. A sound reflecting surface **402**, analogous to sound reflecting surface **103** in FIG. 1, is positioned as illustrated a distance away from the upper edge of the cylindrical housing **405**, such that the upper edge of the cylindrical housing **405** and the sound reflecting surface **402** form a chamber or duct **415** (FIG. 4B) from which sound may emanate, generally perpendicular to the sound reflecting surface **402** as shown by the arrows in FIG. 4B. In the example shown, the sound reflecting surface **402** comprises a circular wall matching the general dimensions of the corresponding end of the cylindrical housing **405**. One or more struts **412**, for example, may attach the sound reflecting surface **402** to the cylindrical housing **405**.

The speaker unit **400** shown in FIGS. 4A and 4B may be of relatively small size and, for example, may be conveniently adapted as desk speakers for a computer or other electronic appliance. The speaker unit **400** may be oriented upwards or downwards, and may provide generally omnidirectional sound output, so that a similar quality of listening experience is provided regardless of which direction the listener is located from the speaker(s). The cylindrical housing **405** and sound reflecting surface **402** may be comprised of a durable material such as, for example, high impact plastic or aluminum, or any other suitable material. While the speaker unit **400** may be advantageously used with, e.g., a computer system, it is not limited to such applications, and may be used in other environments, and may be of any size.

While the speaker housing **405** is illustrated in FIGS. 4A and 4B as a round cylinder, it is not limited to such a shape, and may, for example, be an elliptical cylinder (in which case the speaker **407** may be an elliptical speaker). In other variations, the sound reflecting surface **402** may be replaced by, e.g., a floor or desktop surface, whereby the cylindrical housing **405** is faced downwards with the strut(s) **412** forming a duct or gap between the edge of the speaker **407** and the floor or desktop surface. In yet other embodiments, the strut(s) **412**,

which are shown along the periphery of the top edge of the cylindrical housing **405**, may be replaced by one or more center struts, with a crossbeam (not shown) spanning the diameter of the cylindrical housing **405** and providing a secure footing for the strut(s). In such an embodiment, the strut(s) may generally be attached at or near a centerpoint of the sound reflecting surface **402**. Alternatively, with other variations in crossbeam configurations (which may include off-center crossbeams), the strut(s) may be located in virtually any position desired, although any such crossbeams and/or strut(s) are, in various embodiments, formed with as minimal a profile as possible so as to minimize any interface with the sound output. In other embodiments, the strut(s) may be larger, and may even occupy a significant portion of the circumference of the circular boundary of the sound reflecting surface **402** and cylindrical housing **405**, particularly in those directions in which it is not necessary to have direct sound radiation from the speaker **407**.

Other embodiments may include multiple speaker units of the type illustrated in and described with respect to FIG. 4. For example, a speaker system **500** utilizing cylindrical speaker units **400** of the type shown in FIG. 4, is illustrated in FIG. 5. As shown therein, the speaker system **500** includes a pair of speaker units **400**, connected by a connecting beam **520** which is attached (or attachable) to the top portion of the disk-shaped sound reflecting surface **402** of each of the speaker units **400**. The speaker system **500** may be conveniently hung, for example, from the top of an electronic appliance (not shown) such as a computer monitor, with the connecting beam **520** resting on the top portion of the electronic appliance. A contacting member **525** may be attached to the connecting beam **520** or integral therewith, for providing a resting surface for contacting the top portion of the electronic appliance. The contacting member **525** may be generally flat as illustrated in FIG. 5, or else may, for example, be contoured so as to match the top portion of the electronic appliance. The contacting member **525** may also be used to securably affix the speaker system **500** to the electronic appliance, where the electronic appliance is configured with mechanism for receiving and securing the contacting member **525**. For example, the electronic appliance may be configured with tabs on its top portion for receiving and locking the contacting member **525**. Where a contacting member **525** is not provided as part of the speaker system **500**, and where the connecting beam **520** is generally rod-shaped, the electronic appliance may be configured with a semi-cylindrical molding on its top portion for receiving and holding the connecting beam **520**.

Another embodiment of a narrow profile speaker unit is illustrated in FIG. 13A, which illustrates a top cutaway view of a speaker unit **1300** having two speakers **1307**, **1317**. In the example shown in FIG. 13A, the two speakers **1307**, **1317** are disposed in series along a sound duct **1320** atop a speaker mounting structure such as described previously with respect to, e.g., FIGS. 1 and 2A-2B. The two speakers **1307**, **1317** share a common sound output slot **1306**, similar to the output slot **106** shown in FIG. 1, but the use of multiple speakers may provide advantages such as, for example, increased output capacity, different frequency ranges for different speakers, or other advantages. Similar to the embodiment illustrated in FIG. 3C, sound-damping material **1319** such as compressed foam surrounds the rear contours of the speaker **1317** furthest from the output slot **1306**, and extends to the front of the speaker mounting structure so as to define the sound duct **1320**. The sound duct **1320** is preferably (but not necessarily) of substantially uniform width, generally matching the width of speakers **1307** and **1317**. The speakers **1307** and **1317** may

US 7,433,483 B2

11

be of identical size and audio characteristics, or else, in alternative embodiments, may be of different sizes, shapes, and/or audio characteristics.

FIG. 13B is a simplified block diagram of an electronic circuit 1300 that may be used in, e.g., the speaker arrangement of FIG. 13A, wherein a delay mechanism is used to synchronize sound output between the front and rear speakers relative to the output slot. As shown in FIG. 13B, an audio source signal 1381 is optionally fed into an equalization and/or sound processing unit 1383, which generates an audio output signal 1388. The audio output signal 1388 is applied to the “rear” speaker 1395 (e.g., speaker 1317 in FIG. 13A) via driver 1391 and, though a delay circuit 1385, to the “front” left speaker 1396 (e.g., speaker 1307 in FIG. 13A) via driver 1392. A tweeter or other additional speaker may also be provided. The amount of time delay provided by delay circuit 1385 may be derived, e.g., from the distance between the front speaker 1396 and the rear speaker 1395, given the known velocity of sound travel. The amount of time delay may thus be based upon the center-to-center distance between the rear speaker 1395 and the front speaker 1396, divided by the velocity of sound (about 1116 feet per second). The delay circuit 1385 may take the form of any suitable electronic circuitry (either active or passive, and either analog or digital), and preferably have no impact on the content of the audio output signal 1388, at least over the frequencies being audially reproduced by the speakers 1395, 1396.

Another embodiment of a narrow profile speaker unit 600 is illustrated in FIG. 6, which illustrates a side view of the speaker unit 600 (similar to FIG. 2B). In the example shown in FIG. 6, two speakers 604, 605 are positioned so as to face one another, while they share a common output slot 606 from which their sound radiates. A first mounting surface 602, adapted to receive first speaker 604, is positioned opposite a second mounting surface 603, adapted to receive second speaker 605. The first speaker 604 may, but need not, have identical audio characteristics to second speaker 605. The mounting surfaces 602, 603 define opposing sides of a sound duct 615 having an output slot (or other orifice) 606. A frammel 607, preferably having a non-resonant characteristic, is optionally disposed across the sound duct 615 between the speakers 604, 605, and preferably midway therebetween.

An audio input signal is preferably applied to both speakers 604, 605 simultaneously, such that the speakers 604, 605 simultaneously emit soundwaves towards one another, and against opposite sides of the frammel 607 (if any). As a result, longitudinal soundwaves having the combined power of the outputs of both speakers 604, 605 emanate from output slot 606, thus generating increased audio output, without necessarily requiring the use of a larger (and thus more expensive) driver as may be needed in a single-speaker configuration. If the same audio output signal is applied to both speakers 604, 605, the forces being generated against opposite sides of the frammel 607 will tend to cancel out. Because the output regions of the two speakers 604, 605 are so close together, the potential for undesirable lobing caused by destructive interference from multiple speakers is significantly reduced. By contrast, when the wavelength of the sound output approaches the center-to-center distance between two forward-facing speakers, lobing will tend to occur particularly at off-axis listening positions, but this effect is mitigated by the arrangement of speaker unit 600 in FIG. 6. The “lobeless” characteristic of speaker unit 600 makes it advantageous for use as, e.g., a center channel speaker unit. Moreover, the output slot 606 may generally remain of relatively narrow profile, despite the presence of two speakers 604, 605 which, if forward facing, would tend to occupy substantially more

12

surface area in the direction of sound radiation. The speaker unit 600 of FIG. 6 may provide many of the same benefits of the speaker unit 100 shown in FIG. 1, with the additional benefit of increased sound output. Moreover, the speaker unit 600 may provide an exceptionally robust directional characteristic, with little drop off in volume or frequency response even at extreme angles of listening.

An example of an embodiment in general accordance with the principles described with respect to FIG. 6 is illustrated in FIGS. 28A and 28B, which show a side view in cross-section and an oblique view, respectively, of a speaker unit 2800 enclosing two speakers 2811, 2812 facing one another (although more than two speakers could be present in speaker unit 2800). The speaker unit 2800 comprises a housing 2805 which preferably encloses the speakers 2811, 2812. The speaker housing 2805 in the example illustrated in FIGS. 28A-28B is generally dome-shaped, as illustrated, and rests on a housing base 2809. The speakers 2811, 2812 are disposed on mounting surfaces 2802 and 2803, respectively, in a manner as previously described with respect to FIG. 6. The speaker housing 2805 has an output slot 2821 for sound radiation. The output slot 2821 generally wraps around both sides and the top of the speaker housing 2805, but may be shorter or longer depending upon, e.g., the desired area of sound dispersion or other factors (e.g., aesthetics). In one aspect, the speaker unit 2800 provides a relatively compact, self-contained, and unobtrusive sound output source, which may be conveniently placed on a desktop or shelf, for example, or may be integrated on or atop an electronic appliance.

Another example of an embodiment in general accordance with the principles described with respect to FIG. 6 is illustrated in FIG. 15, which shows a front view of a speaker unit 1500 of multiple pairs of inline speakers facing one another. As illustrated in FIG. 15, there are four pairs of speakers “stacked” in a row, with speakers 1511, 1521 comprising a first pair, speakers 1512, 1522 comprising a second pair, speakers 1513, 1523 comprising a third pair, and speakers 1514, 1524 comprising a fourth pair. Each pair of speakers in FIG. 15 is configured in a manner similar to FIG. 6; that is, the speakers (e.g., 1511, 1521) are facing one another, with a sound output slot (e.g., 1531) therebetween for allowing radiation of the sound from the pair of speakers. The four output slots 1531, 1532, 1533, and 1534 for the four pairs of speakers collectively form an elongated sound output slot; the individual output slots 1531, 1532, 1533, 1534 may optionally be separated by walls 1550. While four pairs of speakers are illustrated in FIG. 15, the same principles of arrangement may be applied to any number of speaker pairs. The use of multiple speaker pairs, such as illustrated in FIG. 15, may provide increased sound output and may therefore be well suited to larger listening environments. At the same time, the speaker profile utilized for sound output may be relatively minimal—e.g., the collective elongate slot formed by output slots 1531, 1532, 1533, and 1534. Thus, the speaker arrangement of FIG. 15 may retain the advantage of providing a relatively unobtrusive and/or narrow profile speaker system, which allows relatively high sound output while providing the ability to conceal the speakers from view, or to provide other speaker packaging options that would otherwise be unavailable.

An example of one such speaker packing option is illustrated in FIG. 16, which depicts a speaker unit 1600 having a cylindrical housing 1607 that may enclose multiple pairs of speakers placed in the general configuration of, e.g., FIG. 15. In FIG. 16, the cylindrical housing 1607 may be placed upright on a surface (such as a room floor), and is securely

US 7,433,483 B2

13

attached to a housing base **1612**, which provides a secure and stable footing for the speaker unit **1600**. An elongate slot (or other orifice) **1606** is provided parallel with the center axis of the cylindrical housing **1607**, and corresponds to the elongate slot collectively formed by output slots **1531**, **1532**, **1533** and **1534** shown in FIG. **15**. The speaker housing **1607** need not have a grille as generally included with conventional speaker units, although a grille could optionally be used to cover output slot **1606**. In addition to aesthetic advantages, and the advantages of having opposing speakers as described with respect to FIGS. **6** and **15**, the speaker unit **1600** may also provide other potential advantages such as, e.g., resistance to weather, since the sound output region is relatively small as compared to conventional speaker units. The shape of the housing **1607** may vary; for example, it may be polygonal in shape, may be domed, or may have flat surfaces along the backsides of the speakers.

Another speaker unit embodiment in accordance with various principles as described herein is illustrated in FIG. **8**, which may be referred to as a ground plane speaker unit **800**, as it may be particularly advantageous for, e.g., improving the sound quality of loudspeakers intended to be placed on a table, desk or similar reflecting surface that is relatively large compared to the wavelength of the radiated sound. The speaker unit **800** is depicted with a dome-shaped housing **805** which, in this example, is comprised of a cylindrical housing member **801** and a dome-shaped top housing member **802** attached to the cylindrical housing member **801**, although both housing members **801**, **802** may be integrated as a singular piece. The speaker unit **800**, shown in cross-sectional side view in FIG. **8**, includes a pair of speakers **807**, **808**—in this example, a first downward facing speaker **807** (preferably a mid-frequency driver having an operating range of about 200 Hz to 2 kHz) and a second downward facing speaker **808** (preferably a high-frequency driver, such as a domed tweeter, having an operating range of about 2 kHz to 20 kHz) disposed below the first speaker **807**. The speaker **807** is mounted on a mounting surface **812**, and faces a spacer **821** which provides a sound reflecting surface **803**. The mounting surface **812** and sound reflecting surface **803** define a chamber or duct **815**, similar to the speaker units described with respect to, e.g., FIGS. **1** and **4A-4B**. Sound output from speaker **807** generally emanates perpendicular to the sound reflecting surface **803** and to the face of the speaker **807**. Similarly, speaker **808** is oriented in a downwards direction, towards a housing base **824** (or other smooth surface) which acts as a sound reflecting surface, and defines a second chamber or duct **819** from which sound may emanate, generally perpendicular to the orientation of the downward-facing speaker **808**. Speaker unit **800** thus has two annular output slots corresponding to ducts **815** and **819**, one output slot for each speaker **807**, **808**.

The spacer **821** may have a top plate (not separately shown) of, e.g., particle board or MDF material, to provide a reflective surface for the top speaker **807**, and may otherwise be comprised of any of a variety of materials or compositions, such as foam, polyurethane, silicone, composites, or other materials.

The speaker housing **805** may be connected to the spacer **821** via one or more strut(s) **814**, in a manner similar to that described with respect to FIGS. **4A-4B**. Likewise, the spacer **812** may be connected to the housing base **821** via one or more strut(s) **824**, in a manner similar to that described with respect to FIGS. **4A-4B**. As with the speaker unit shown in FIGS. **28A-28B**, the speaker unit **800** of FIG. **8** may provide a relatively compact, self-contained, and unobtrusive sound

14

output source, which may be conveniently placed on a desktop or shelf, for example, or may be integrated on or atop an electronic appliance.

A speaker unit **800** configured in accordance with the principles of FIG. **8** may provide improved listening experience in a variety of circumstances. FIGS. **10A** and **10B** are illustrations comparing the radiance of sound from a ground plane speaker unit **800** constructed in accordance with the principles of FIG. **8**, with a conventional two-way speaker unit **1012**. With a conventional two-way speaker unit **1012**, a high frequency driver **1019** is often placed above a mid-frequency driver **1017** within the speaker enclosure. When the speaker **1012** is placed on a surface (particularly a highly reflective surface such as a desktop, or a hard floor) **1022**, a listener (represented by point **1026** in FIG. **10A**) generally experiences both a direct sound output from the speakers **1017**, **1019** as well as a reflected sound output caused by the surface **1022**. It can be seen from FIG. **10A** that there will be a differential time delay due to the path difference between the direct sound and the first reflection. For differential delay times comparable with the period of the signal frequency, the resulting phase differences are sufficient to cause destructive interference between the direct and reflected sound spectra often referred to as “comb filtering.” The resulting spectral distortions can impart a roughness or coloration to the perceived sound quality. Comb filtering effects can be lessened by raising the speakers above the desk on a stand, but the benefit of this adjustment is generally offset by the loss in low frequency output since useful reinforcement of the low frequencies that would otherwise be provided by the reflecting surface **1022** is reduced.

By contrast, as illustrated in FIG. **10B**, a speaker unit **800** in accordance with the embodiment illustrated in FIG. **8** may retain low frequency enhancement while avoiding comb filtering effects. In the arrangement of FIG. **8**, the differential time delay may be sufficiently reduced to avoid destructive interference over the whole of the audio band, improving the sound quality from the standpoint of a typically positioned listener **1056**. The mid-frequency driver **807** is sufficiently close to the reflecting surface **1052** that low frequency boost is retained, and the radiating apertures defined by ducts **815**, **819** are preferably close enough to the sound reflecting surface **1052** that an interfering phase shift between the direct and reflecting soundwaves is not induced. In addition, the speaker unit **800** of FIG. **8** may possess an extremely broad directional characteristic over the frequency range for which the wavelength of sound in air is large compared with the slot dimensions.

In variations of the embodiment shown in FIG. **8**, the speaker housing **805** need not be dome-shaped but may take on a variety of other shapes; for example, it may be cylindrical, pyramidal (including in the shape of a wide obelisk), or polygonal. The speaker unit **800** may also be oriented in a different direction; for example, it may be oriented upwards, with the speaker housing **805** suitably shaped to provide a stable base surface. As illustrated in the example of FIG. **8**, the width of the aperture or gap defined by duct **819** for the high frequency driver (speaker **808**) may be narrower than the width of the aperture or gap defined by the duct **815** for the mid-frequency driver (speaker **807**). However, while exemplary dimensions are illustrated in FIG. **8** for the width of the ducts **815** and **819** (10 and 8 millimeters respectively), and for the width of the spacer **821** (12 millimeters), these dimensions are by no means intended to be limiting, but are merely exemplary.

In other variations of the speaker unit **800** illustrated in FIG. **8**, the position of the second speaker **808** may be varied,

US 7,433,483 B2

15

and/or sound damping material may be used to, e.g., control the directivity of the sound output from the second speaker **808**. FIGS. **9A** through **9E** are top view cross-sectional diagrams illustrating various arrangements of relative speaker locations and sound damping material, as may be used in connection with the speaker unit illustrated in FIG. **8**. FIG. **9A** is a bottom view illustrating a situation in which the lower speaker **808** (illustrated as **903** in FIG. **9A**) is centrally disposed within spacer **821** (illustrated as **901** in FIG. **9A**), much as shown in and described with respect to FIG. **8**. FIG. **9B** illustrates a similar configuration but with the lower speaker **913** off-set from the center axis of the spacer **911**. FIG. **9C** is similar to FIG. **9A**, with the lower speaker **923** centrally disposed with respect to spacer **921**, but sound damping material **926** is added in duct **819** such that sound is output through a slot or aperture **925**. FIG. **9D** is similar to FIG. **9B**, with the lower speaker **933** offset from the center axis of spacer **931**, but sound damping material **936** is added in the duct (as with FIG. **9C**) such that sound is output through a slot or aperture **935**. FIG. **9E** is similar to FIG. **9C**, with the lower speaker **943** centrally disposed with respect to spacer **941**, but sound damping material **946**, **948** has been added such that two output slots or apertures **945**, **947** are defined through which sound from the speaker **943** may be output. Thus, placement of the lower speaker **808** may be varied, and/or sound damping material added to provide various sound output strategies.

The speaker unit **800** illustrated in FIG. **8**, and its other variations as described herein, may be useful in a variety of applications in addition to desktop or floor standing loudspeakers. For example, such a speaker unit may be used in recording studios to avoid undesired sound reflections and interference from a mixing desk. The speaker unit may be mounted to a wall or ceiling, in the manner of a smoke alarm, providing exceptional omnidirectional sound quality but with an unobtrusive appearance. The speaker unit could also be used on electronic appliances, such as attached to a plasma or flatscreen television monitor, or a desktop computer monitor, or the like.

Various embodiments as disclosed herein pertain to narrow profile speaker arrangements in which two (or possibly more) speakers are placed side-by-side or in near proximity. Examples of such embodiments are illustrated in, e.g., FIGS. **11**, **12B**, and **19A**, and elsewhere herein. In some of these embodiments, it is possible, with suitable sound processing of left and right audio input signals, to achieve a spreading of the sound image to produce a stereo-like quality despite the fact that the speakers may be closely spaced. Such speaker systems may find useful application in a variety of environments, such as, e.g., automobiles or desktop computers.

When a pair of speakers are closely spaced, they may be placed on a common mounting structure—for example, in a common enclosure, with a central (preferably airtight) dividing partition—that may, for example, be inserted into or else integral with the front console or dashboard of an automobile, or placed elsewhere near the central axis of the automobile, or placed in a suitable location in another confined space or listening environment. FIGS. **12A**, **12B** and **12C** illustrate one example of an enclosure **1201** as part of a speaker system **1200**, particularly suited to applications where space is limited, housing a pair of speakers **1214**, **1215** which can receive and respond to sound processed signals from left and right audio channels in accordance with the various techniques described elsewhere herein. FIG. **12A** is a front cut-away view of the exemplary speaker enclosure **1201** housing the pair of speakers **1214**, **1215**; FIG. **12B** is a top cross-sectional view of the speaker enclosure **1201** shown in FIG. **12A**; and FIG. **12C** is an oblique front view of the speaker enclosure

16

1201 shown in FIGS. **12A** and **12B**. As shown perhaps best in FIG. **12C**, the speaker enclosure **1201** in this example is preferably substantially rectangular in shape, and, where configured for an automobile, is preferably designed with dimensions so as to slide into or otherwise fit within a standard or double “DIN” slot in the front console space of an automobile. The speaker enclosure **1201** may include a front panel **1232**, a pair of side panels **1230**, a top panel **1235**, a bottom panel **1239**, and possibly a back panel **1231**. To achieve isolation between the two speakers **1214**, **1215**, an interior wall **1216** such as illustrated in FIG. **12A** and **12B** may be placed between the speakers **1214**, **1215**, thus creating two separate speaker chambers, one housing each of the two speakers **1214**, **1215**. The speakers **1214**, **1215** are preferably positioned or mounted on a baffle, a mounting surface, or other barrier so as to acoustically isolate their rear radiation from their front radiation.

The pair of speakers **1214**, **1215** may be oriented with the speaker faces directed frontwards; however, in the instant example, the speakers **1214**, **1215** are oriented downwards, as illustrated in FIG. **12A**. When so oriented, a slot (or other orifice) **1219** may be located at the bottom of the speaker enclosure **1201**, to allow the sound from the speakers **1214**, **1215** to radiate outwards towards the direction of the listeners in the automobile. Effectively, then, the speakers **1214**, **1215** only take up an amount of console/dash surface space corresponding to the size of the slot **1219**. In an automobile environment, front console/dash space is typically extremely valuable since it is scarce, and thus the ability to position two speakers **1214**, **1215** in the front console/dash while minimizing the amount of surface space consumed can be quite advantageous. Audio system controls/display(s) or other conventional console accouterments (controls, LCD or other displays, air vents, etc.) can be attached to or integral with the front panel **1232** of the speaker enclosure **1201**, so the available surface space on the front panel **1232** is valuably utilized.

Moreover, when oriented in the manner described above, the speakers **1214**, **1215** may be potentially larger in size (assuming console space is limited); for example, each speaker may be about 4" (for a total of approximately 8" across collectively), which may fit into a standard DIN space or other similar space, whereas the speakers would otherwise generally have to be under perhaps 2" to 2½" or less to fit within the DIN space (or other similar center console space), if oriented in a frontwards direction. The ability to place larger speakers in the center speaker unit may, among other advantages, allow better bass reproduction than would be the case with smaller centrally located speakers and, hence, can reduce or potentially dispense with the need for side (e.g., door-mounted) bass speakers to carry the bass information of the left and right channels.

The effect of orienting the speakers **1214**, **1215** in a downward direction is conceptually illustrated in FIG. **12D**, which shows a generic speaker **1290** pointing downwards towards a surface **1291**. The sound output from the speaker **1290** radiates outward from the centerpoint along the surface **1291** in essentially all directions (i.e., a complete 360-degree circle). Thus, as shown in FIGS. **12A** and **12C**, a slot **1219** is preferably located at the bottom of the speaker enclosure **1201**, to allow the sound from the speakers **1214**, **1215** to radiate outwards towards the direction of the listeners in the automobile. A layer of insulation **1212** (e.g., foam or other sound-damping material) matching the outer contours of the speakers **1214**, **1215**, as illustrated in FIG. **12B** or in other embodiments as shown elsewhere herein, may be placed within the speaker enclosure **1201**, so that the sound does not reflect on the back panel **1231** (if any) of the speaker enclosure.

US 7,433,483 B2

17

sure. In the resulting speaker enclosure configuration, sound emanating from the speakers **1214**, **1215** is cleanly projected through the slot **1219** to the listeners in the automobile.

The layer of insulation **1212** may have the benefit(s) in certain embodiments of preventing the creation of standing waves, and/or of minimizing the variation of sound output response with respect to frequency so that the speaker output can be readily equalized by, e.g., any standard techniques, including analog or digital equalization. For example, cascaded filter sections may be employed to tailor the frequency response of the speakers **1214**, **1215** in discrete frequency bands so as to provide a relatively uniform overall frequency response.

The layer of insulation **1212** may be comprised of any suitable material, preferably non-resonant in nature and having sound damping or absorbing qualities. The insulation **1212** may, for example, be comprised of expanded or compressed foam, but may alternatively comprise rubber, reinforced paper, fabric or fiber, damped polymer composites, or other materials or composites.

In an alternative embodiment, the speakers **1214**, **1215** may be directed upwards instead of downwards, with the slot **1219** being located at the top of the speaker enclosure **1201**, to achieve a similar effect. The speakers **1214**, **1215** may alternatively be positioned sideways, either facing towards or away from each other, with a pair of slots (one for each of the speakers **1214**, **1215**) being adjacent and vertical in orientation rather than horizontal, as with slot **1219**. In such an embodiment, the speaker enclosure may be taller but narrower in size.

In some circumstances, high frequencies (such as over 2 KHz) might become lost or reduced in the speaker enclosure configuration illustrated in FIGS. **12A-12C**. Therefore, one or more additional speakers **1217** of small size (e.g., tweeters) may be advantageously placed above the "bell" of the speakers **1214**, **1215** and in the front panel **1232** of the speaker enclosure **1201**, to radiate the higher frequencies.

FIG. **14** is a block diagram of a sound processing system **1400** as may be used, for example, in connection with the speaker system **1200** illustrated in FIGS. **12A-12D**, or more generally in other sound systems which utilize multiple audio channels to provide stereo source signals to closely spaced speakers. In the sound processing system **1400** of FIG. **14**, a left audio signal **1411** and right audio signal **1412** are provided from an audio source and processed to provide left and right output signals **1448**, **1449** for closely spaced speakers **1424**, **1425**, and may be fed to other speakers as well (not shown in FIG. **14**). A difference between the left audio signal **1411** and right audio signal **1412** is obtained by, e.g., a subtractor **1440**, and the difference signal **1441** is preferably fed to a spectral weighting filter **1442**, which applies a spectral weighting (and possibly a gain factor) to the difference signal **1441**. The characteristics of the spectral weighting filter **1442** may vary depending upon a number of factors including the desired aural effect, the spacing of the speakers **1424**, **1425** with respect to one another, the taste of the listener, and so on. The output of the spectral weighting filter **1442** may be provided to a phase equalizer **1445**, which compensates in part for the phase shifting effect caused by the spectral weighting filter **1442** (if non-linear).

The output of the phase equalizer **1445** in FIG. **14** is provided to a cross-cancellation circuit **1447**. The cross-cancellation circuit **1447** also receives the left audio signal **1411** and right audio signal **1412**, as adjusted by phase compensation circuits **1455** and **1456**, respectively. The phase compensation circuits **1455**, **1456**, which may be embodied as, e.g., all-pass filters, shift the phase of their respective input signals

18

(i.e., left and right audio signals **1411**, **1412**) in a complementary manner to the phase shifting performed by the phase equalizer **1445** (and the inherent phase distortion caused by the spectral weighting filter **1442**). The cross-cancellation circuit **1447**, which may include a pair of summing circuits (one for each channel), then mixes the spectrally-weighted, phase-equalized difference signal, after adjusting for appropriate polarity, with each of the phase-compensated left audio signal **1411** and right audio signal **1412**. The perceived width of the soundstage produced by the pair of speakers **1424**, **1425** can be adjusted by varying the gain of the difference signal path, and/or by modifying the shape of the spectral weighting filter **1442**.

FIG. **29** is a diagram of a sound processing system **2900** in general accordance with the principles and layout illustrated in FIG. **14**, having a pair of closely spaced speakers **2924**, **2925**, and further showing typical examples of possible transfer function characteristics for certain processing blocks. As with FIG. **14**, in the sound processing system **2900** a left audio signal **2911** and a right audio signal **2912** are provided from an audio source (not shown), and a difference signal **2941** is obtained representing the difference between the left audio signal **2911** and the right audio signal **2912**. The difference signal **2941** is fed to a spectral weighting filter **2942**, which, in the instant example, applies a spectral weighting to the difference signal **2941**, the characteristics of which are graphically illustrated in the diagram of FIG. **29**. A more detailed graph of the this example appears in FIG. **30A**. As shown therein, the spectral weighting filter **2942** is embodied as a first-order shelf filter with a gain of 0 dB at low frequencies, and turn-over frequencies at approximately 200 Hz and 2000 Hz. If desired, the gain applied by gain/amplifier block **2946** can be integrated with the spectral weighting filter **2942**, or the gain can be applied downstream as illustrated in FIG. **29**. In any event, the turnover frequencies, amount of gain, slope, and other transfer function characteristics may vary depending upon the desired application and/or overall system characteristics.

A phase equalizer **2945** is provided in the center processing channel, and addition phase compensation circuits **2955** and **2956** in the right and left channels, to ensure that the desired phase relationship is maintained, over the band of interest, between the center channel and the right and left channels. As shown graphically in both FIG. **29** and in more detail in FIG. **30A**, the spectral weighting filter **2942** in the instant example causes a phase distortion over approximately the 200 Hz to 2000 Hz range. The phase equalizer **2945** provides no gain, but modifies the overall frequency characteristic of the center channel. The phase compensation circuits **2955** and **2956** likewise modify the phase characteristics of the left and right channels, respectively. The phase compensation is preferably selected, in the instant example, such that the phase characteristic of the center channel (that is, the combined phase effect of the spectral weighting filter **2942** and the phase equalizer **2945**) is approximately 180° out-of-phase with the phase characteristic of the left and right channels, over the frequency band of interest (in this example, over the 200 Hz to 2000 Hz frequency band). At the same time, the phase characteristic of the left and right channels are preferably remains the same, so that, among other things, monaural signals being played over the left and right channels will have identical phase processing on compensation circuits **2955** and **2956** preferably are configured to apply identical phase processing to the left and right channels.

More detailed graphical examples of gain and phase transfer functions (with the gain being zero in this case when the components are embodied as all-pass filters) are illustrated

for the center channel phase equalizer **2945** in FIG. **30B** and for the left and right channels phase compensation circuits **2955**, **2956** in FIG. **30C**. In these examples, the phase equalizer **2945** is embodied as a second-order all-pass filter (with $F=125$ Hz and $Q=0.12$), and the phase compensators **2955**, **2956** are each embodied as second-order all-pass filters (with $F=3200$ Hz and $Q=0.12$). A higher Q value may be used to increase the steepness of the phase drop-off, reducing the extent to which the center channel is out-of-phase with the left and right channels at low frequencies (thus minimizing the burden imposed upon the speakers **2924**, **2925**).

The sound processing systems **1400** and **2900** of FIGS. **14** and **29** may provide certain benefits, such as a broadened sound image, when used in connection with two closely spaced speakers such as illustrated in FIGS. **12A-12C**. Also, while the speaker enclosure **1201** shown in FIGS. **12A-12C** has certain advantages for placement in a standard DIN space (or other similar or analogous space) of an automobile, it should be understood that the closely spaced speakers **1214**, **1215**, whether or not contained in a speaker enclosure **1201**, may be positioned in other areas of the automobile as well, such as atop the front dashboard, above the rear seatback, or in a center console or island located between the front seats or between the front and back seats. Preferably, the closely spaced speakers **1214**, **1215** are located on or near the center axis of the automobile, so as to provide optical sound quality evenly to occupants on both sides.

Because of space constraints within an automobile, centrally located speakers may have to be of limited size. Smaller speakers, however, tend to suffer losses at low frequencies. To compensate for the loss of low frequency components where the central pair of speakers are small, left and right bass speakers may be provided in a suitable location—for example, built into the automobile doors. The left and right audio channels fed to the left and right door speakers can be processed to attenuate the mid/high frequencies and/or boost the bass audio components. Providing bass frequencies through the door speakers will not destroy the stereo effect of the mid/high frequencies provided by the central pair of speakers, since low frequencies are not normally localized by the human listener. In addition, a sub-woofer may be added in a suitable location within the automobile to further enhance very low frequency bass audio components. The sub-woofer may be located, for example, in the rear console of the car above the rear seatback, or in any other suitable location.

Various modifications may be made to provide even further improved sound for passengers in the back seat area. For example, a similar pair of closely spaced speakers to those placed in the front console or area can also be placed in the rear of the automobile, for example, atop the rear seatback on or in the rear parcel shelf, or at the back structure of the center island or console/armrest between the driver and passenger seats. The same signals that are used to feed the front pair of closely spaced speakers can be used to feed the rear pair of closely spaced speakers. If desired, a speaker enclosure **1201**, such as shown in FIGS. **12A-12C**, containing the pair of closely spaced speakers may be placed in the rear of the vehicle to house these rear speakers.

In certain applications, it may be desirable to provide surround sound or other multi-channel capability in a vehicular automotive system, in conjunction with a closely spaced speaker arrangement such as described previously herein. For example, a van, SUV or other large vehicle may have a DVD system which allows digital audio-visual media to be presented to the passengers of the vehicle, with the sound potentially being played through the vehicle audio system. In other cases, it may be desirable to allow for extreme right and left

directional sound, which may originate by the existence of left and right surround channels on the recorded medium, or simply by the presence of an extreme and intentional disparity in the relative volumes of the left and right channel.

The mounting structure for the closely spaced speakers may take any of a wide variety of forms. In general, any mounting structure that provides adequate support for the closely spaced speakers (and possibly other components, including additional speakers, discrete electrical components, and/or printed circuit board(s)) and which forms a relatively narrow or constrained orifice for sound output from the closely spaced speakers may be utilized in the various embodiments as described herein. FIG. **23A**, for example, is a diagram of a speaker mounting structure as may, for example, be used in connection with the speaker enclosure **1200** illustrated in FIGS. **12A-12D**, or else in other arrangements. In FIG. **23A**, speakers **1214'** and **1215'** (which are generally analogous to speakers **1214** and **1215** illustrated in FIG. **12A**) are mounted on a baffle comprising a speaker mounting plate **1239** which, in this example, forms a top surface of sound ducts or channels associated with speakers **1214'** and **1215'**, respectively. Along with the speaker mounting plate **1239**, a sound reflecting plate **1238'**, side plates **1230'**, an optional center divider **1216'**, and a back plate (not shown) generally define the sound ducts or channels which output sound from slots **1219a** and **1219b**. The baffle (speaker mounting plate **1239**) serves to reduce interference between sound radiated from the front and rear of the speakers **1214'**, **1215'**. As indicated previously, with respect to, e.g., FIG. **12B**, compressed or expanded foam, or other sound-damping material, may be placed within portions of the sound ducts to help guide the sound output in the desired direction while reducing undesirable artifacts and acoustic interference.

In certain applications, it is preferred that the other interior surfaces of top plate **1239**, bottom plate **1238'** or side plates **1230'** are constructed of a rigid and substantially non-resonant material such as molded or high-impact plastic, pressed steel, aluminum, ceramics, and the like, or composite materials such as mica- or glass-reinforced plastic. The top plate **1239**, bottom plate **1238'** and side plates **1230'** are preferably thin to minimize the space needed for the speaker unit assembly **2300**. Likewise, the center divider **1216'**, if provide, may also be constructed of a rigid and substantially non-resonant material.

The rigid and substantially non-resonant interior surfaces of the sound ducts or channels are helpful in propagating the acoustic waves generated by speakers **1214'**, **1215'** through the ducts or channels and out of output slots **1219a** and **1219b** while minimizing losses due to absorption, but may also in some cases cause undesirable interference, cancellation, standing waves, or acoustic artifacts. The embodiment illustrated in FIG. **19A** may mitigate these potential problems. FIG. **19A** is a cutaway top view diagram of a speaker mounting structure, similar in certain respects to FIG. **12B**. As shown in FIG. **19A**, sound-damping material **1912** is extended to the front **1932** of the speaker mounting structure **1901**, thereby forming sound ducts **1959**, **1960** associated with each of the two speakers **1914**, **1915**.

FIG. **19B** shows the general dimensions of sound duct **1959** or **1960**, with portions of the speaker mounting plate **1939** and sound reflecting plate **1938** defining two surfaces of the sound duct **1959** or **1960**, and two sides **1961**, **1962** of the sound duct **1959** or **1960** being defined by the edge of the sound-damping material **1912** (shown in FIG. **19A**). An opening in the speaker mounting plate **1939** (i.e., baffle) permits placement of the speaker **1914** or **1915** thereon. In one aspect, the sound duct **1959** or **1960** effectively “turns”

the sound output by the speaker **1914** or **1915** by 90° (in this example), so that the sound is carried to the output slot and released while retaining a sufficient degree of sound quality, and, similar to a number of other embodiments described herein, modifies the effective shape of the speaker output from an elliptical or circular radiator to a rectangular radiator. In addition, the total radiating surface area can be advantageously reduced, as compared to the radiating surface area of the speakers themselves, minimizing the space needed in the vehicle dash or other locations of the vehicle or other environment. Moreover, the aspect ratio of the output slot can be adjusted or tailored to modify the directional characteristic of the acoustic output in order to, for example, make the sound image broader along a particular axis, thus improving sound quality at off-axis listening positions.

The sound duct(s) **1959**, **1960** may, in alternative embodiments, be slightly or moderately ascending or descending, or else the passage or duct may be semi-curved, such that the direction of the sound output is modified. Also, in various embodiments, the output slot may flare outwards or else may have other variations in size, shape (e.g., may be ovoid), and uniformity.

As illustrated in FIGS. **19A** and **19B**, the sound ducts **1959**, **1960** may be of substantially the same width as the cones of the speakers **1914**, **1915**, and may provide a superior mechanism for transporting the acoustical output of the speakers **1914**, **1915** through the output slots **1919**, **1920**, respectively, as compared, for example, with a rectangular duct having only hard and reflective surfaces. Variations in the size and shape of the sound ducts **1959**, **1960**, as noted above, may be made while still achieving superior or at least acceptable sound output quality. An example of another speaker unit **1100** with closely spaced speakers, shown in cutaway top view in FIG. **11**, is similar in certain respects to FIG. **19**, but the sound damping material **1119** is tapered towards the front of the speaker mounting structure **1104**, thereby forming sound ducts **1106**, **1116** associated with each of the two speakers **1107**, **1117** which gradually widen towards the front of the speaker mounting structure **1104**. Other variations in the shaping of the sound damping material **1119** are possible as well.

Like the central partition **1216** (FIGS. **12A-2C**) or **1216'** (FIG. **23A**), the central strip or section **1913** of the sound-damping material **1912** shown in FIG. **19** (or the analogous portion of the sound damping material **1119** shown in FIG. **11**) may help prevent interference between the acoustic output of the left and right speakers **1914**, **1915**, provided that the sound-damping material **1912** in the central strip or section **1913** is dense enough to effectively isolate the sound ducts **1959**, **1960** from one another. The central strip of section **1913** of the sound-damping material **1912** may further provide the advantage of eliminating or lessening the severity of standing waves that could, in certain embodiments, develop due to the particular shape or nature of the sound ducts **1919**, **1920**, and the presence of a more sound-reflective central partition. The sound-damping material **1912** preferably has sufficient acoustic absorption so as to reduce or eliminate the possible buildup of standing waves. By eliminating a more reflective central partition (such as **1216** in FIGS. **12A-12C** or **1216'** in FIG. **23B**) and replacing it with a central strip or section **1913** of sound-damping material **1912**, the effective width of the central strip or section **1913** can be effectively doubled (as compared to simply adding sound-damping material to either side of the central partition **1216** or **1216'**), thus potentially improving its ability to counteract the buildup of standing waves. Moreover, the sound-damping material **1912** in its entirely preferable helps minimize the variation of

sound output response with respect to frequency so that the output of speakers **1914**, **1915** can be readily equalized by, e.g., any standard techniques, including analog or digital equalization. For example, cascaded filter sections may be employed to tailor the frequency response of the speakers **1914**, **1915** in discrete frequency bands so as to provide a relatively uniform overall frequency response.

FIG. **23B** illustrates one particular embodiment of a speaker mounting structure in accordance with certain principles described with respect to FIGS. **19A** and **19B**. As illustrated in FIG. **23B**, speakers **1914**, **1915** may be disposed on a baffle comprising speaker mounting plate **1939** (which is a top plate in this example). A sound reflecting plate **1938** (the bottom plate in this example) is positioned in a generally parallel orientation with respect to the speaker mounting plate **1939**, and is separated therefrom by a layer of sound-damping material **1912** such as compressed foam. Rigid side panels **1930**, or alternatively struts or other rigid members along the sidewall regions and/or, if desired, within the sound-damping material **1912**, may optionally be provided for mechanical support. The front of speaker mounting structure illustrated in FIG. **23B** may be compared against that shown in FIG. **23A**, which does not show sound-damping material extending substantially to the front of output slots **1219a**, **1219b**.

A speaker system in accordance with principles and concepts as disclosed herein may include more than two speakers. Various embodiments, for example, utilize multiple speakers in each of the left and right channels, with the multiple speakers in each channel outputting sound through a common sound duct or channel and out an orifice (such as an aperture or slot). Examples of such embodiments are illustrated in FIGS. **17A-17C**, **20**, and **22**. In the embodiment shown in FIGS. **17A** and **17B**, multiple (two in this example) speakers **1714a**, **1714b** are disposed in series along a sound duct **1759** on one side of the speaker mounting structure **1701**, and, likewise, multiple (two in this example) speakers **1715a**, **1715b** are disposed in series along a sound duct **1760** on the other side of the speaker mounting structure **1701**. In effect, each of the left and right audio channels has multiple speakers, which may provide advantages such as, for example, increased output capacity, different frequency ranges for different speakers, or other advantages. Similar to the embodiment illustrated in FIG. **19**, sound-damping material **1712** such as compressed foam surrounds the rear contours of the speakers **1714a** and **1715a** furthest from the output slots **1719**, **1720**, and extends to the front **1732** of the speaker mounting structure **1701** so as to form left and right sound ducts **1759**, **1760**. The sound ducts **1759**, **1760** are preferably (but not necessarily) of substantially uniform width, generally matching the width of speakers **1714a**, **1714b** and **1715a**, **1715b**. The speakers **1714a**, **1714b**, **1715a**, **1715b** may be of identical size and audio characteristics, or else, in alternative embodiments, may be of different sizes, shapes, and/or audio characteristics.

FIG. **17B** illustrates a cutaway side view of the speaker mounting structure **1701** shown in FIG. **17A**, with speakers **1714a** (or **1715a**) and **1714b** (or **1715b**) shown in side profile. The speakers **1714a**, **1714b**, **1715a**, **1715b** are mounted upon a baffle comprising a speaker mounting surface **1739**. The speaker mounting surface **1739** and a sound reflecting surface **1738**, which are preferably rigid and substantially non-resonant in nature, define sound ducts **1759**, **1760** and allow propagation of the acoustic output of speakers **1714a**, **1714b**, **1715a**, **1715b** through output slots **1719**, **1720**. The shape of the sound-damping material **1712**, generally in this example following the rear contours of the furthest speakers **1714a**, **1715a** from the output slots **1719**, **1720**, tends to improve the

US 7,433,483 B2

23

quality of the output sound by preventing expansion of the sound waves in a rearward direction, and thereby reducing potential interference or other undesirable acoustic effects. While FIG. 17B shows an enclosure surrounding speakers 1714a, 1714b, 1715a, 1715b, such an enclosure is not necessary and can be omitted.

In some situations, depending in part upon the size and shape of the sound ducts 1759, 1760 and the nature of the audio material, it may be possible for standing waves to develop within the sound ducts 1759, 1760 which adversely impact the quality of the audio output. The particular dimensions of the sound ducts 1759, 1760 and length, width, and/or thickness of the sound-damping material 1712 can be optimized by experimentation in order to yield the optimal sound quality for a given type of speakers 1714a, 1714b, 1715a, 1715b, a given audio track or type of audio material, compositions or materials used to form the speaker mounting structure (such as those used to form the rigid interior surfaces and/or the sound-damping material), and so on, by eliminating cross-modes and lengthwise modes associated with standing waves in the sound ducts 1759, 1760.

FIG. 17C illustrates an example of preferred dimensions for the sound-damping material 1712' where four speakers 1714a', 1714b', 1715a', and 1715b' are used in speaker assembly of the type generally illustrated in FIG. 17A. As shown in FIG. 17C, the amount of sound-damping material 1712' that is placed to either side of a sound duct 1759' or 1760' may be approximately W/8, where W represents the outer width boundaries of the sound-damping material 1712' for a given channel. With two channels, the sound-damping material 1712' may be combined in the center portion between the two sound ducts 1759', 1760', yielding a collective width of approximately W/4, as illustrated in FIG. 17C. Similarly, the amount of sound-damping material 1712' that is placed at the rear of each sound duct 1759', 1760' may be approximately L/5 to L/4, where L represents the outer length boundaries of the sound-damping material 1712' for a given channel (assuming the sound-damping material 1712' extends to the edge of slots 1719', 1720').

The particular dimensions illustrated in FIG. 17C are simply representative of one example. In practice, it may be expected that good results with respect to sound quality may be obtained over ranges of different widths of sound-damping material 1712' placed to either side of a sound duct 1759' or 1760' and to the rear of the further speakers 1714a', 1714b' from the slots 1719', 1720'. Moreover, similar parameters may be applied, as appropriate, to embodiments having a single row of speakers such as the one shown in, e.g., FIG. 19A.

Returning to FIGS. 17A and 17B, the thickness of the sound-damping material 1712 is preferably sufficient to fill the volume (except for the sound ducts) between the surface mounting plate 1739 and sound reflecting plate 1738 without gaps that might cause cross-mode interference or the creation of sound artifacts, and thus may generally be dictated by the distance of separation of the surface mounting plate 1739 and the sound reflecting plate 1738. Typically, the thickness of the sound-damping material 1712 might be in the range of, e.g., 1/2" to 1" thick, although the thickness may vary depending upon the size and shape of the relevant portions of the speaker mounting structure 1701.

While the size and shape of the sound ducts 1759, 1760 and output slots 1719, 1720 may vary depending upon the particular design preferences for the vehicle sound system, there may be physical or practical limitations to how narrow the sound ducts 1759, 1760 or output slots 1719, 1720 may be made. Narrowing of the sound ducts 1759, 1760 or output

24

slots 1719, 1720 may decrease the efficiency of the speakers (which may be compensated by larger speakers and/or increased drive power), and may cause audible noise from turbulence. Therefore, the narrowness of the sound duct or slot size may be limited by, among other things, impedance losses that cannot be made up by increased drive power and the onset of sound artifacts or noise caused by turbulence or nonlinear airflow.

While the embodiment illustrated in FIGS. 17A-17C shows two speakers in series for each channel, the same principles may be extended to any number of speakers in series in each speaker channel.

FIG. 20 is a cutaway top-view diagram of another speaker arrangement similar to FIG. 17A but adding an additional speaker. The layout of the speaker mounting structure 2001 shown in FIG. 20 is similar to that of FIG. 17A, with "rear" speakers 2014a, 2015a and "front" speakers 2014b, 2015b placed over left and right sound ducts 2059 and 2060 as illustrated. An additional speaker 2017, such as, e.g., a domed tweeter, is added between the left and right sound ducts 2059, 2060, and the sound-damping material 2012 (e.g., compressed or expanded foam) is preferably formed so as to define a central sound duct 2061, which in this example is relatively short. In the case where the additional speaker 2017 is a tweeter or else handles significant high frequency signal components, it is generally desirable to place the speaker 2017 as near to the output slot 2021 as possible. The additional speaker 2017 may have a relatively narrow output slot 2021, for example, 6-8 millimeters in height. Where available space is a concern, or where it is desired to achieve certain specific dimensions of sound-damping material surrounding the left and right sound ducts 2059, 2060, the sound ducts 2059, 2060 may be tapered slightly towards the sound output slots 2019, 2020 in order to accommodate the central sound duct 2061. In alternative embodiments, the sound ducts 2059, 2060 may not be tapered. The central sound duct 2061 may flare outwards as it extends towards the central output slot 2021 so as to provide a relatively broad directional characteristic.

One potential advantage of using speaker output slots 2019, 2020, and 2021 (and similar configurations in other embodiments disclosed herein), is that the effective radiation sources of the speakers can be brought closer together, leading to a cleaner, smoother sound image both on and off axis, and reducing the potential for destructive interference or other undesirable sound distortion due to perceptible time delays between the left and right acoustic output. Moreover, in certain embodiments, the perceptible sound output may be stable and not fall off at relevant frequencies regardless of the listener's relative position along the narrower axis of the slot(s) 2019, 2020 and 2021 (or at least not until approximately 90 degrees off angle), such that the speaker system provides uniform and wide coverage of substantially all the listening area in a near omnidirectional manner.

FIG. 21 is an oblique view diagram in general accordance with the speaker arrangement of FIG. 20, illustrating one possible embodiment of a speaker mounting structure associated therewith. As shown in FIG. 21, a baffle comprising a speaker mounting plate 2139 may define several openings for placement of various the speakers 2114a, 2114b, 2115a, 2115b (and optionally 2117). The speaker mounting plate 2139 may be physically attached to a sound reflecting plate 2138 by multiple struts 2185 placed at, e.g., the corners and/or along the sides of each of the speaker mounting plate 2139 and the sound reflecting plate 2138. Advantageously, a compressible sound-damping material 2112, such as foam, may be placed between the speaker mounting plate 2139 and the

sound reflecting plate **2138** and compressed therebetween. To facilitate compression of the sound-damping material **2112**, the struts **2185** may take the form of threaded bolts which may be screwed into threaded holes (not shown) aligned in the speaker mounting plate **2139** and sound reflecting plate **2138**. Tightening the threaded bolts has the effect of compressing the sound-damping material **2112**. As previously described, the sound-damping material **2112** may be used to form sound ducts for the speakers **2114a**, **2114b**, **2115a**, **2115b**, **2117** which terminate in sound output slots **2119**, **2120**, and **2121** as shown. A similar technique for constructing a speaker mounting structure may be applied to the various other embodiments described herein, including for example, those illustrated in FIGS. **12A-12B** and **17A-17C**, or others.

FIG. **22** is an assembly diagram of a speaker unit **2201** utilizing a general speaker arrangement such as shown in FIG. **20**. As illustrated in FIG. **22**, the speaker unit **2201** includes a baffle comprising a speaker mounting structure **2288** which has several openings for placement of speakers **2214**, **2215** (and optionally **2217**). In this particular example, the speaker mounting structure **2288** has a speaker mounting plate around the periphery of which are walls surrounding the speakers **2214**, **2215**, **2217**, but such walls may not be necessary or desired in other embodiments. A sound reflecting plate **2287** is configured to generally match the bottom dimensions of the speaker mounting structure **2288**. Sound-damping material **2212**, **2213** may be preformed in one or more pieces to define sound ducts for the various speakers **2214**, **2215**, **2217**, and is preferably compressed or expanded between sound reflecting plate **2287** and the speaker mounting enclosure **2288**. In this particular example, a speaker enclosure ceiling **2283** is adapted for placement atop the speaker mounting structure **2288**, thereby forming a speaker enclosure. The speaker enclosure ceiling **2283** may have multiple holes through which, e.g., threaded bolts may be inserted for ultimate securing to the sound reflecting plate **2287**, which may have threaded holes in matching alignment with the holes in the speaker enclosure ceiling **2283**. As previously described, tightening of the threaded bolts may advantageously provide compression of the sound-damping material **2212**, **2213**.

With the speaker unit **2201** of FIG. **22**, or with other embodiments described herein, it may be desirable to package one or more speakers, sound processing electronics or components for the speakers, and, if desired, other electronics (such as a receiver, amplifiers, onboard computer, etc.) in a single discrete unit that may be conveniently installed in a vehicle as, e.g., a substitute for a vehicle's existing in-dash stereo unit. FIG. **24** is a diagram showing an example of a stereo unit **2400** adapted for convenient installation in a vehicle. In the example of FIG. **24**, the stereo unit **2400** includes an enclosure **2401** housing two or more internal speakers (not shown) which radiate sound via output slots **2419** and **2420** (illustrated with speaker grills which may be added for aesthetic purposes). Internally, the stereo unit **2400** may contain, e.g., two speakers with foam-surrounded sound ducts similar to the arrangement illustrated in FIG. **19A** and/or **23B**. On any available space of a front panel **2439** of the stereo unit **2400** may be placed a display **2481** and various controls, buttons and/or knobs **2482** and **2483** which may be found on conventional in-dash stereo units. In addition to the speakers, the stereo unit **2400** may contain electronics such as a receiver, amplifier(s), equalizers, sound processing components, etc., to provide the functionality of an in-dash stereo unit. The enclosure **2401** of the stereo unit may be of appropriate dimension to fit within a standard (single or double) DIN slot or other similar or analogous space, to allow convenient substitution of a vehicle's existing stereo unit. The

stereo unit **2400** may also have various electrical connections or ports (not shown) to allow electrical connection to external speakers or other electronic components in the vehicle.

Additional details relating to closely spaced speaker configurations and sound processing relating thereto may be found in, e.g., U.S. application Ser. Nos. 10/339,357 and 10/074,604, and PCT Application Ser. No. PCT/US02/03880, each of which is assigned to the assignee of the present invention, and all of which are incorporated herein by reference as if set forth fully herein.

It should be emphasized that, while various embodiments have been illustrated in the drawings with the speakers positioned or mounted on the apparent "top" of the speaker mounting assembly or speaker enclosure, the speaker mounting assembly may be placed in any desired orientation. Thus, where terms such as "top" and "bottom" or "left" and "right" are used herein, they are not meant to convey absolute orientation but rather relative orientation with respect to a reference frame that may be rotated or otherwise manipulated. The speaker mounting assembly may be placed in any suitable orientation such that, for example, the sound output slots are vertical rather than horizontal, or the speaker mounting surface is below the sound reflecting surface.

Where speakers are placed in series such as shown, for example, in the embodiments illustrated in FIGS. **17A-17C**, **20**, and **21**, interference between the speakers may potentially occur due to the fact that the "front" speakers (e.g., **1714b**, **1715b**) are closer to their respective output slots (e.g., **1719**, **1720**) than the "rear" speakers (e.g., **1714a**, **1715a**). As a result, sound from the rear speakers takes longer to propagate down the sound duct and emanate out of the output slot than with the front speakers. Because the acoustic output from the front and rear speakers are delayed relative to one another, the sound waves can interfere and lead to destructive cancellation of as much as 10 dB or possibly more, or can lead to other anomalies. In order to prevent the "delayed" output from the rear speakers causing destructive interference with the output from the front speakers or other undesirable effects, it may be desirable to add a delay to the drive signal feeding the front speakers, such that the sound output is synchronized relative to the output slot. In addition to delaying the signal to the forward speakers **1714b**, **1715b**, the power level for the rearward speakers **1714a**, **1715a** may be increased.

FIG. **18** is a simplified diagram of a circuit **1800** that may be used in, e.g., the speaker arrangements of FIGS. **17A-17C** or FIG. **20**, wherein delays are used to synchronize sound output between the front and rear speakers relative to the output slots. As shown in FIG. **18**, left and right channel audio signals **1811**, **1812** are fed into a sound processor **1810**, as described elsewhere with respect to, e.g., FIG. **14** or **29**, and modified left and right channel audio signals **1848**, **1849** are generated. The left channel audio signal **1848** is applied to the "rear" left speaker **1814a** (via driver **1891**) and, though a delay **1881**, to the "front" left speaker **1814b** (via driver **1892**). Similarly, the right channel audio signal **1849** is applied to the "rear" right speaker **1815a** (via driver **1893**) and, through a delay **1882**, to the "front" right speaker **1815b** (via driver **1894**). If a tweeter **1817** (or other additional speaker) is provided, then the appropriate audio signal **1847** may be provided to the tweeter **1817** through a delay **1883** and driver **1895**. The delays **1881**, **1882**, and **1883** may be derived from the distance between each front speaker **1814b**, **1815b** and its respective rear speaker **1814a**, **1815a**, given the known velocity of sound travel. For example, assuming the left and right channels are symmetrical in layout, the delays **1881**, **1882** are preferably based upon the center-to-center distance of the rear speaker **1814a**, **1815a** to the front speaker **1814b**,

US 7,433,483 B2

27

1815b, divided by the velocity of sound (about 1116 feet per second). Analogously, the delay **1883** for the tweeter **1817** is preferably based upon the center-to-center distance of the tweeter **1817** to the front speakers **1814b**, **1815b** along the lengthwise axis of the sound ducts. The delays **1881**, **1882**, **1883** may take the form of any suitable electronic circuitry (either active or passive), and preferably have no impact on the content of the audio signals **1847**, **1848**, **1849**, at least over the frequencies being audially reproduced by the speakers.

While the example illustrated in FIG. **18** shows a particular system configuration, it will be appreciated that other variations may be made as well drawing upon similar principles. For example, rather than having five drivers **1891-1895**, one for each speaker **1814a**, **1814b**, **1815a**, **1815b**, and **1817**, fewer drivers (e.g., three) or more may be used, with, for example, a single driver being shared by two speakers (e.g., **1814a** and **1814b**).

In one aspect, an automotive sound system is provided which encompasses a combination of speaker configuration, speaker placement, and sound processing to reduce or minimize the undesired sonic effects of the inevitable asymmetries between the listeners and speaker positions in a car or similar vehicle, and to provide more uniform sound for all the occupants. A pair of speakers, or two (or more) rows of speakers, are preferably placed close together and located in the front of the console or dashboard with their geometric center on, or as near as possible to, the central axis of symmetry of the vehicle. A sound processor acts to "spread" the sound image produced by the two closely spaced speakers by employing a cross-cancellation technique in which the cancellation signal is preferably derived from the difference between the left and right channels. The resulting difference signal is scaled, delayed (if necessary), and spectrally modified before being added to the left channel and, in opposite polarity, to the right channel. The pair of speakers may be placed on a common mounting surface, and/or in a common housing enclosure having a slot for allowing sound to emanate. Additional bass speakers may be added (in the doors, for example) to enhance bass sound reproduction.

In various embodiments as described herein, improved sound quality results from creation of a sound image that has stability over a larger area than would otherwise be experienced with, e.g., speakers spaced far apart without comparable sound processing. Consequently, the audio product can be enjoyed with optimal or improved sound over a larger area, and by more listeners who are able to experience improved sound quality even when positioned elsewhere than the center of the speaker arrangement. Thus, for example, an automobile or vehicular sound system may be capable of providing quality sound to a greater number of listeners, not all of whom need to be positioned in the center of the speaker arrangement in order to enjoy the rendition of the particular audio product.

It will be appreciated that a drive unit or speaker system having sound radiated through a slot or aperture can be useful with a single channel or speaker, as well as with multiple channels or speakers, even apart from the use of signal processing to, e.g., modify or improve the sound output of two closely spaced centrally located speakers. For example, one or more speakers may be located in a central slotted speaker enclosure or arrangement with or without added signal processing to produce a widened sound image or similar effects. Similarly, one or more speakers may be located in a slotted speaker enclosure or arrangement on the left and/or right sides of the vehicle, or in other locations (along the central axis or otherwise), in order to provide speaker outputs having a minimized output profile or minimized radiating surface area. A drive unit or speaker configured in such a manner may

28

have improved visual appearance, take up less surface area, and/or provide an improved directional characteristic (which can be particularly important if the speaker is located at other than ear level).

Another embodiment of a speaker system is illustrated in FIG. **25**, which illustrates a top-view cross-sectional view of an array of speakers **2507** each having individual sound output slots **2506**. The speaker system **2500** of FIG. **25**, in one aspect, expands upon the basic arrangement depicted in FIG. **19A**, by offering an arbitrary number of speakers **2507** arranged in a linear array. The speakers are separated by sound damping material **2519** which, in the manner described with respect to FIG. **19A** and other similar embodiments herein, defines sound output slot(s) **2506** for directing the radiation of sound output by the speakers **2507**. The speakers **2507** may be mounted to a baffle or other mounting surface as previously described herein.

FIGS. **26A** and **26B** illustrate a potential application of the speaker array illustrated in FIG. **25**. FIG. **26A** shows a cross-sectional side view of a flatscreen display device **2600** (such as a flatscreen or plasma television, or a computer monitor), while FIG. **26B** shows a front view thereof. The display device **2600** has a housing **2602** with a screen **2621**, which are collectively mounted on a stand **2605**. A speaker array comprised of speakers **2607** are arranged linearly along the top-side of the display device housing **2602**, facing upwards, with their respective output slots **2606** forming an elongate output slot. Similarly, smaller speaker arrays comprised of speakers **2617** are arranged linearly along the bottom side of the display device housing **2602**, facing downwards, with their respective output slots **2616** forming elongate output slots on either side of the stand **2605**. The illustrated speaker arrangement requires significantly less surface area than a conventional arrangement of forward-facing speakers, and the cones of the speakers **2607**, **2617** may be advantageously concealed behind the body of the housing **2602**, as illustrated, thus keeping the depth of the display device **2600** minimal. The output slots **2606**, **2616** may be covered with, e.g., a grille or perforated mesh to conceal their presence. Sound processing may optionally be added to the signals provided to speakers **2607**, **2617** in the various speaker arrays, to account for the different speaker positions. Of course, the number of speakers **2607**, **2617** and the relative positions of the speaker arrays may be varied according to the needs of a particular design. For example, the speaker arrays could be located along the left and right sides of the display device housing **1602**. Moreover, the speakers **2607** and/or **2617** could be arranged as speaker pairs, similar to the inline speaker unit depicted in FIG. **15**, at the expense of perhaps increased height or vertical dimension of the display device housing **2602**. However, such an arrangement could potentially double the number of speakers available for use.

FIG. **27** illustrates another embodiment, in an oblique view, of a speaker unit **2700** having an array of speakers **2707** and sound output slot(s). In FIG. **27**, speakers **2707** form a linear array as generally described with respect to FIG. **25**, with the addition of a high frequency speaker (e.g., tweeter) **2715** which is centrally located in the speaker array. A contoured region of sound damping material **2719** (compressed foam or other suitable material) surrounds the periphery of the tweeter **2715**, and may also be used (although not shown) to surround the other speakers **2707** in a similar manner, such as previously described with respect to FIG. **25**. An elongate output slot **2705** radiates the sound from the various speakers **2707**, **2715**, according to similar principles as previously described herein with respect to a number of other embodiments.

US 7,433,483 B2

29

In any of the foregoing embodiments, the audio product from which the various audio source signals are derived, before distribution to the various automobile speakers or other system components as described herein, may comprise any audio work of any nature, such as, for example, a musical piece, a soundtrack to an audio-visual work (such as a DVD or other digitally recorded medium), or any other source or content having an audio component. The audio product may be read from a recorded medium, such as, e.g., a cassette, compact disc, CD-ROM, or DVD, or else may be received wirelessly, in any available format, from a broadcast or point-to-point transmission. The audio product preferably has at least left channel and right channel information (whether or not encoded), but may also include additional channels and may, for example, be encoded in a surround sound or other multi-channel format, such as Dolby-AC3, DTS, DVD-Audio, etc. The audio product may also comprise digital files stored, temporarily or permanently, in any format used for audio playback, such as, for example, an MP3 format or a digital multi-media format.

The various embodiments described herein can be implemented using either digital or analog techniques, or any combination thereof. The term "circuit" as used herein is meant broadly to encompass analog components, discrete digital components, microprocessor-based or digital signal processing (DSP), or any combination thereof. The invention is not to be limited by the particular manner in which the operations of the various sound processing embodiments are carried out.

While examples have been provided herein of certain preferred or exemplary sound processing characteristics, it will be understood that the particular characteristics of any of the system components may vary depending on the particular implementation, speaker type, relative speaker spacing, environmental conditions, and other such factors. Therefore, any specific characteristics provided herein are meant to be illustrative and not limiting. Moreover, certain components, such as the sound processor described herein with respect to various embodiments, may be programmable so as to allow tailoring to suit individual sound taste.

While certain system components are described as being "connected" to one another, it should be understood that such language encompasses any type of communication or transference of data, whether or not the components are actually physically connected to one another, or else whether intervening elements are present. It will be understood that various additional circuit or system components may be added without departing from teachings provided herein.

In any of the embodiments described herein, the speakers utilized in the sound system may be passive or active in nature (i.e., with built-in or on-board amplification capability). The various audio channels may be individually amplified, level-shifted, boosted, or otherwise conditioned appropriately for each individual speaker or pair of speakers.

While preferred embodiments of the invention have been described herein, many variations are possible which remain within the concept and scope of the invention. Such variations would become clear to one of ordinary skill in the art after inspection of the specification and the drawings. The invention therefore is not to be restricted except within the spirit and scope of any appended claims.

What is claimed is:

1. A narrow profile sound system, comprising:

a drive unit disposed on a mounting surface, said mounting surface forming a barrier acoustically isolating the drive unit's forward radiation from its rearward radiation;
a sound reflecting surface facing the drive unit and substantially parallel with the mounting surface; and

30

sound damping material disposed between said sound reflecting surface and the mounting surface, the sound reflecting surface and the mounting surface defining a bottom and top of a narrow sound duct terminating in an elongate output slot, with the sound damping material forming sides of the sound duct, whereby forward radiation from the drive unit is turned at a substantially right angle and channeled along a straight path towards the output slot;

wherein the sound damping material forms an outer shape of the sound duct which reduces sound reflections at the end of the sound duct opposite the output slot and thereby mitigates standing waves.

2. The narrow profile sound system of claim 1, wherein sound emanating from the output slot is characterized by a wide horizontal dispersion angle and a narrow vertical dispersion angle as a result of the elongate shape of the output slot.

3. The narrow profile sound system of claim 1, wherein said sound damping material forms a back wall of the sound duct, said back wall substantially following a curved contour of a portion of a drive unit cone farthest opposite from the output slot.

4. A narrow-profile groundplane audio speaker system, comprising:

a speaker housing;

a first drive unit disposed within said speaker housing, said first drive unit mounted on a baffle whereby the drive unit's forward radiation is isolated from its rearward radiation; and

one or more support members separating said first drive unit from a first sound reflecting surface facing said first drive unit;

wherein the baffle and the first sound reflecting surface define a sound duct terminating in a first sound output aperture proximate an outer edge of said first drive unit; whereby forward radiation from said first drive unit is substantially unimpeded in the direction of the first sound reflecting surface, and is turned at a substantially right angle and travels along a straight path to exit the first sound output aperture; and

wherein said first sound output aperture is sufficiently narrow such that an interfering phase shift is avoided between the direct and reflecting sound waves output from said first drive unit.

5. The audio speaker system of claim 4, wherein said first sound reflecting surface is substantially parallel with the baffle on which said first drive unit is mounted.

6. The audio speaker system of claim 4, wherein said first drive unit comprises a mid-range drive unit.

7. The audio speaker system of claim 4, wherein said first sound output aperture provides omnidirectional sound output for said first drive unit.

8. The audio speaker system of claim 4, wherein said sound output aperture is elongate, and wherein sound emanating from the sound output aperture is characterized by a wide horizontal dispersion angle and a narrow vertical dispersion angle as a result of the elongate shape of the sound output aperture.

9. The audio speaker system of claim 4, wherein said first drive unit is disposed within an enclosure of said speaker housing, and wherein said one or more support members comprises a plurality of struts connecting the enclosure to the sound reflecting surface, whereby the sound reflecting surface is disposed in front of said first drive unit.

10. The audio speaker system of claim 4, wherein said sound reflecting surface is substantially flat.

US 7,433,483 B2

31

11. The audio speaker system of claim 4, wherein said speaker housing is configured to rest stably on a flat surface such that said first drive unit faces towards the flat surface.

12. The audio speaker system of claim 11, wherein said speaker housing is rounded with an apex above the central axis of said first drive unit.

13. The audio speaker system of claim 4, wherein said speaker housing is domed.

14. The audio speaker system of claim 4, wherein said speaker housing comprises a cylindrical portion, wherein said first drive unit is axially centered in said cylindrical portion, and wherein said baffle is disposed at one end of said cylindrical portion.

15. The audio speaker system of claim 11, wherein said first drive unit faces downwards towards the flat surface, and wherein the sound output from said first sound output aperture radiates horizontally in a substantially omnidirectional pattern.

16. The audio speaker system of claim 4, wherein said baffle is substantially level with a top edge of the first sound output aperture.

17. The audio speaker system of claim 4, wherein said first drive unit is disposed about 1 cm from the first sound reflecting surface.

18. A narrow-profile groundplane audio speaker system comprising:

a speaker housing;

a first drive unit disposed within said speaker housing, said first drive unit mounted on a baffle whereby the drive unit's forward radiation is isolated from its rearward radiation;

one or more support members separating said first drive unit from a first sound reflecting surface facing said first drive unit; and

sound damping material disposed between the first sound reflecting surface and the baffle;

wherein the baffle and the first sound reflecting surface define a sound duct terminating in a first sound output aperture;

whereby forward radiation from said first drive unit is turned at a substantially right angle and travels along a straight path to exit the first sound output aperture;

wherein said first sound output aperture is sufficiently narrow such that an interfering Phase shift is avoided between the direct and reflecting sound waves output from said first drive unit;

wherein the sound damping material forms sides of the sound duct; and

wherein the sound output aperture is located at the termination of the sides of the sound duct, whereby forward radiation from the drive unit is channeled along a straight path towards said sound output aperture.

19. The audio speaker system of claim 18, wherein the sound damping material forms an outer shape of the sound duct which reduces sound reflections at the end of the sound duct opposite the sound output aperture and thereby mitigates standing waves.

20. The audio speaker system of claim 18, wherein said sound damping material forms a back wall of the sound duct, said back wall substantially following a curved contour of a portion of a cone of said drive unit farthest opposite from the sound output aperture.

21. A narrow-profile groundplane audio speaker system, comprising:

a speaker housing having an enclosure portion and a base portion;

32

a drive unit disposed within the enclosure portion of said speaker housing, said drive unit mounted on a baffle whereby the drive unit's forward radiation is isolated from its rearward radiation; and

one or more support members separating said drive unit from a substantially flat sound reflecting surface facing said drive unit;

wherein the baffle and the sound reflecting surface define a sound duct terminating in a sound output aperture;

whereby forward radiation from said drive unit is turned at a substantially right angle and travels along a straight path to exit the sound output aperture;

wherein said sound output aperture is sufficiently narrow such that an interfering phase shift is avoided between the direct and reflecting sound waves output from said drive unit; and

wherein said speaker housing is adapted to rest stably on a flat surface such that said drive unit faces towards the flat surface.

22. The narrow-profile groundplane audio speaker system of claim 21, wherein said speaker housing is rounded with an apex above the central axis of said first drive unit.

23. The narrow-profile groundplane audio speaker system of claim 22, wherein said speaker housing is domed.

24. The narrow-profile groundplane audio speaker system of claim 21, wherein said sound reflecting surface forms the top of said base portion, and wherein said base portion is substantially flat.

25. The narrow-profile groundplane audio speaker system of claim 21, wherein the enclosure portion of said speaker housing comprises a cylindrical base section, wherein said drive unit is axially centered in said cylindrical base section, and wherein said baffle is disposed at one end of said cylindrical base section.

26. The narrow-profile groundplane audio speaker system of claim 25, said drive unit faces downwards towards the flat surface, and wherein the sound output from said sound output aperture radiates horizontally in a substantially omnidirectional pattern with respect to the center axis of said drive unit.

27. The narrow-profile groundplane audio speaker system of claim 21, wherein said speaker housing rests stably on the flat surface such that said drive unit faces downwards towards the flat surface.

28. The narrow-profile groundplane audio speaker system of claim 21, wherein said sound duct has a top edge substantially level with an outer edge of a cone of said drive unit.

29. The narrow-profile groundplane audio speaker system of claim 21, wherein the baffle is substantially level with a top edge of the sound output aperture.

30. The narrow-profile groundplane audio speaker system of claim 21, wherein the drive unit is disposed about 1 cm from the sound reflecting surface.

31. A narrow-profile groundplane audio speaker system, comprising:

a speaker housing;

a drive unit enclosed within said speaker housing, said drive unit mounted on a baffle whereby the drive unit's forward radiation is isolated from its rearward radiation, said speaker housing being adapted to rest stably on a flat surface such that said drive unit faces towards the flat surface;

a sound reflecting surface facing said drive unit; and

one or more support members separating said drive unit from said sound reflecting surface;

wherein the baffle and the sound reflecting surface define a sound duct terminating in a sound output aperture;

US 7,433,483 B2

33

whereby forward radiation from said drive unit is turned at a substantially right angle and travels along a straight path to exit the sound output aperture;

wherein said sound output aperture is sufficiently narrow such that an interfering phase shift is avoided between the direct and reflecting sound waves output from said drive unit; and

wherein said sound output aperture is lengthwise proximate the flat surface, whereby sound output is increased without substantial loss in smoothness or evenness of response over audio frequency ranges.

32. The narrow-profile groundplane audio speaker system of claim **31**, further comprising sound damping material dis-

34

posed between said sound reflecting surface and the baffle, the sound damping material forming an outer shape of the sound duct which reduces sound reflections at an end of the sound duct opposite the sound output aperture and thereby mitigates standing waves.

33. The narrow-profile groundplane audio speaker system of claim **31**, wherein said drive unit faces downwards towards the flat surface, and wherein the sound output from said sound output aperture radiates horizontally in a substantially omnidirectional pattern.

* * * * *